

# MIRD Pamphlet No. 14 Revised: A Dynamic Urinary Bladder Model for Radiation Dose Calculations

Stephen R. Thomas, Michael G. Stabin, Chin-Tu Chen and Ranasinghage C. Samaratunga

A Task Group of the MIRD Committee, Society of Nuclear Medicine

*Department of Radiology, University of Cincinnati College of Medicine, Cincinnati, Ohio; Oak Ridge Associated Universities, Oak Ridge, Tennessee; and University of Chicago, Chicago, Illinois*

The constant-volume urinary bladder model in the standard MIRD Pamphlet No. 5 (Revised) phantom has recognized limitations. Various investigators have developed detailed models incorporating more physiologically realistic features, such as expanding bladder contents and residual volume, and variable urinary input rate, initial volume and first void time. We have reviewed these published models and have developed a new model for calculation of radiation absorbed dose to the urinary bladder wall incorporating these aspects. **Methods:** The model consists of a spherical source with variable volume to simulate the bladder contents and a wall represented by a spherical shell of constant volume. The wall thickness varies as the source expands or contracts. The model provides for variable urine entry rate (three different hydration states), initial bladder contents volume, residual volume and first void time. The voiding schedule includes an extended nighttime gap during which the urine entry rate is reduced to one-half the daytime rate. **Results:** Radiation-absorbed dose estimates have been calculated for the bladder wall surface (including photon and electron components) and at several depths in the wall (electron component) for  $2\text{-}^{18}\text{F}$ -fluoro-2-deoxy-D-glucose,  $^{99m}\text{Tc}$ -diethylenetriaminepentaacetic acid (DTPA),  $^{99m}\text{Tc}$ -HEDP,  $^{99m}\text{Tc}$ -pertechnetate,  $^{99m}\text{Tc}$ -red blood cells (RBCs),  $^{99m}\text{Tc}$ -glucoheptonate,  $^{99m}\text{Tc}$ -mercaptoacetyl/triglycerine chelator (MAG3),  $^{99m}\text{Tc}$ -methylene diphosphonate (MDP),  $^{99m}\text{Tc}$ -hexamethylpropylene amine oxime (HMPAO),  $^{99m}\text{Tc}$ -human serum albumin (HSA),  $^{99m}\text{Tc}$ -MIBI (rest and stress),  $^{123}\text{I}$ -/ $^{124}\text{I}$ -/ $^{131}\text{I}$ -OIH,  $^{123}\text{I}$ / $^{131}\text{I}$ -Nal,  $^{125}\text{I}$ -iothalamate,  $^{111}\text{In}$ -DTPA and  $^{89}\text{Sr}$ -SrCl. **Conclusion:** The new model tends to give a higher radiation absorbed dose to the bladder wall surface than the previous models. Large initial bladder volumes and higher rates of urine flow into the bladder result in lower bladder wall dose. The optimal first voiding time is from 40 min to 3 hr postadministration, depending on radiopharmaceutical. The data as presented in tabular and graphic form for each compound provide guidance for establishing radiation absorbed dose reduction protocols.

**Key Words:** dosimetry; urinary bladder radiation absorbed dose; dynamic bladder; MIRD dose calculation

*J Nucl Med* 1999; 40:102S-123S

## FOREWORD TO REVISED MIRD PAMPHLET NO. 14

The theoretical concepts and output calculations for the radiation absorbed dose to the urinary bladder wall were published originally as MIRD Pamphlet No. 14, "A Dynamic Urinary Bladder Model for Radiation Dose Calculations" (1). After publication, the authors discovered an error in the computer code used to generate the output values, which introduced an

Received Feb. 26, 1998; revision accepted Jun. 29, 1998.

For correspondence contact: Stephen R. Thomas, PhD, E560 Medical Sciences Building, University of Cincinnati, College of Medicine, Cincinnati, OH 45267-0579.

For reprints contact: Evelyn E. Watson, MS, Chair, MIRD Committee, 104 New Bedford Lane, Oak Ridge, TN 37830.

This is the last in a series of MIRD Special Contributions.

error in the calculated results with a magnitude dependent on the radionuclide as well as the specific model parameters. The values published originally were ~40% low (ranging from < 10% low to > 60% low). In addition, typographical errors were identified in the expressions involving the model description. The MIRD Committee recognized the importance of rectifying this situation and announced the preparation of a revised pamphlet (2), which would provide corrections and also take the opportunity to expand the list of radiopharmaceuticals presented. The requisite corrections and changes have been implemented in this revision along with the inclusion of eight additional radiopharmaceuticals thus providing results for a total of 19 agents used both diagnostically and therapeutically. For some of the original radiopharmaceuticals, the biologic parameters have been updated through new references and/or revised kinetic modeling analysis, which also has introduced modifications in the calculated results.

## INTRODUCTION

Calculation of radiation absorbed dose (hereafter referred to as "radiation dose" or simply "dose") to the inner mucosal surface and at depth in the urinary bladder wall from radioactivity distributed within the bladder contents is of importance for:

- Evaluating new or existing radiopharmaceuticals for human use; and
- Designing patient protocol strategies intended to minimize the radiation dose for a specific radiopharmaceutical.

Accurate radiation dose estimates may hold particular significance for those agents that are excreted rapidly, such as  $2\text{-}^{18}\text{F}$ -fluoro-2-deoxy-D-glucose (FDG) (3,4) and  $^{99m}\text{Tc}$ -diethylenetriaminepentaacetic acid (DTPA) (4).

Most dose estimates to the bladder wall are based on the standard MIRD 5 (Revised) phantom, in which the bladder has a constant volume (5). No provision is made for dynamic variation or incorporation of other variables (such as filling rate, initial volume, residual volume, first voiding time and wall thinning) that may be expected to have an effect on the dose. The limitations of this bladder model have long been recognized and various alternative models have been proposed. In this paper, the published models for the urinary bladder are reviewed, and the results are compared with those provided under equivalent conditions by the original MIRD model. A new model was developed that incorporates the complexities of

**TABLE 1**  
Definition of Symbols Used in the Calculational Methods Described in Table 2

Symbol	Name/description	Units*	
		Traditional	S.I.
$\bar{A}$	Cumulated activity, $\bar{A} = \int A(t)dt$	$\mu\text{Ci} \cdot \text{h}$	$\text{MBq} \cdot \text{s}$
$A(t)$	Activity within the bladder at time t	$\mu\text{Ci}$ (or mCi)	$\text{MBq}$
$A_v(t)$	Bladder activity per unit volume at time t	$\mu\text{Ci}/\text{cm}^3$ (or mCi/cm <sup>3</sup> )	$\text{MBq}/\text{cm}^3$
$\bar{D}/A_0$	Average dose to the bladder wall [or dose to the inner surface] per unit administered activity	$\text{rad}/\mu\text{Ci}$ (or rad/mCi)	$\text{mGy}/\text{MBq}$
$D_v(V)$	Photon dose to the bladder wall at bladder volume V	rad	mGy
$f_{\text{f},i}$	Residual bladder volume fraction following a void [the i <sup>th</sup> void]	—	—
$g_s$	Geometrical factor for a point on the surface of a sphere	cm	cm
$r(t)$	Bladder radius at time t	cm	cm
$R_{ss}$	Electron dose rate at the bladder wall inner surface per unit activity in the bladder contents volume	$\text{rad}/\text{mCi} \cdot \text{h}$	$\text{mGy}/\text{MBq} \cdot \text{s}$
$R_{ys}$	Photon (gamma) dose rate at the bladder wall inner surface per unit activity in the bladder contents volume	$\text{rad}/\text{mCi} \cdot \text{h}$	$\text{mGy}/\text{MBq} \cdot \text{s}$
$R_{yw}$	Average photon (gamma) dose rate within the bladder wall per unit activity in the bladder contents volume	$\text{rad}/\text{mCi} \cdot \text{h}$	$\text{mGy}/\text{MBq} \cdot \text{s}$
$S$	S value for the bladder contents (source) to the bladder wall (target)	$\text{rad}/\mu\text{Ci} \cdot \text{h}$	$\text{mGy}/\text{MBq} \cdot \text{s}$
$T_v$	Regular voiding interval	h	s
$T_i$	Void time for the i <sup>th</sup> void	h	s
$T_1$	Time of first void	h	s
$U(t)$	Urine volume rate of entry into the bladder	ml/min (or cm <sup>3</sup> /min)	ml/s (or cm <sup>3</sup> /s)
$V(t)$	Bladder volume at time t	ml (or cm <sup>3</sup> )	ml (or cm <sup>3</sup> )
$V(T_i)$	Bladder volume prior to i <sup>th</sup> void at time $T_i$	ml (or cm <sup>3</sup> )	ml (or cm <sup>3</sup> )
$V_o$	Initial bladder contents volume	ml (or cm <sup>3</sup> )	ml (or cm <sup>3</sup> )
$V_r$	Residual volume following void	ml (or cm <sup>3</sup> )	ml (or cm <sup>3</sup> )
$X(t)$	Gamma ray exposure rate at the inner bladder wall surface at time t	R/h	C/kg · s
$\alpha_j$	Biologic coefficients representing the fraction of the administered activity entering the bladder for the j <sup>th</sup> component	—	—
$\Delta_\beta$	Mean electron particle energy emitted per nuclear transition (formerly equilibrium dose constant)	$\text{rad} \cdot \text{g}/\mu\text{Ci} \cdot \text{h}$	$\text{mGy} \cdot \text{kg}/\text{MBq} \cdot \text{s}$
$\lambda_j$	Biologic rate constant for entry of the j <sup>th</sup> component into the bladder	$\text{h}^{-1}$	$\text{s}^{-1}$
$\lambda$	Physical decay constant	$\text{h}^{-1}$	$\text{s}^{-1}$
$\rho$	Density of the medium	g/ml (or gm/cm <sup>3</sup> )	g/cm <sup>3</sup>
$\tau$	Residence time in the bladder contents	h	s
$\Gamma$	Exposure rate constant	$\text{R} \cdot \text{cm}^2/\text{mCi} \cdot \text{h}$	$\text{C} \cdot \text{cm}^2/\text{kg} \cdot \text{MBq} \cdot \text{s}$
$\Gamma'$	Exposure rate constant converted to dose in tissue using the roentgen-to-rad or coulomb/kg-to-mGy conversion factor	$\text{rad} \cdot \text{cm}^2/\text{mCi} \cdot \text{h}$	$\text{mGy} \cdot \text{cm}^2/\text{MBq} \cdot \text{s}$
$\mu$	Effective photon absorption coefficient for water at a given energy	$\text{cm}^{-1}$	$\text{cm}^{-1}$

\*Care must be taken to use the correct conversion factors (h or s to min,  $\mu\text{Ci}$  to mCi, g to kg and so on) when applying the units in Table 1 to Equations 1-3 (see Calculational Methods).

urinary function into a practical algorithm for calculating the radiation dose to the bladder wall.

#### REVIEW OF PREVIOUSLY PUBLISHED URINARY BLADDER MODELS FOR DOSIMETRY CALCULATIONS

Table 1 contains definitions of symbols used in the algorithms of four previously published urinary bladder models for dose calculations that are described in Table 2, along with the new model. Model A in Table 2 is associated with the standard MIRD 5 (Revised) phantom (5). [Other information that is relevant to the MIRD schema and model descriptions are provided in references (6-10).] A limitation of the model is that the volume of the bladder contents remains constant at 202.6 ml (200 g). The surface electron dose rate is derived from the approximation that the dose rate at the surface of a large sphere is one-half of the dose rate in an infinite medium that has the same radioactive concentration as within the sphere (11). The photon dose is derived using Monte Carlo techniques. Bladder wall dose per unit cumulated activity in various source organs,

including bladder contents, has been calculated for many radionuclides with this model (10). Cumulated activity in bladder contents is derived using a bladder radioactivity input model, which is generally obtained from the whole-body retention curve determined through knowledge of the pharmaceutical biokinetics. No attempt is made to represent the physical dynamics of bladder filling and emptying.

Snyder and Ford (12) developed a model in which the bladder is represented as an ellipsoid with axes in the ratio of 4:3:3 (left-right:front-back:top-bottom) that remains fixed as the bladder fills (Model B in Table 2). The surface electron dose rate is also derived using the assumption that the dose rate at the surface of a sphere is one-half of the dose rate in the infinite medium. The variation of electron dose rate with depth is estimated using an integration of Berger's (13,14) point kernel for an infinite slab of finite thickness with a semi-infinite source on one side. An average electron dose to the wall was calculated, as was a surface electron dose. Photon dose is

**TABLE 2**  
Descriptive Details of Urinary Bladder Models for Dosimetry Calculations

Model	Anatomic configuration	Physiologic aspects	Calculational methods	Comments
A. MIRD 5 (Revised) (1978) (5)	1. Ellipsoid of constant volume (bladder contents): 202.6 ml (200 g) 2. Wall mass = 45.13 g (volume = 45.73 ml) 3. Wall thickness: constant in time but varies geometrically according to position relative to ellipse axes (i.e., thickest along the direction of the major axis)	1. Activity input is derived from the whole-body retention curve 2. Variable but regularly spaced void intervals traditionally taken as 2.4 hr or 4.8 hr (corresponding to 10 or 5, respectively, equally spaced voiding times over a 24-hr period)	1. $R_{\beta S} = \Delta_\beta / (2\rho V(t))$ 2. $R_{\gamma W}$ : Derived empirically using Monte Carlo calculations 3. $\tau = \bar{A}/A_0$ $\sum_j \alpha_j \left[ \frac{1 - e^{-\lambda T_V}}{\lambda} - \frac{1 - e^{-(\lambda_j + \lambda)T_V}}{\lambda_j + \lambda} \right] \times \left[ \frac{1}{1 - e^{-(\lambda_j + \lambda)T_V}} \right]$ 4. $\bar{D}/A_0 = S\tau$	1. The beta dose rate is derived from the standard assumption that the dose rate at the surface of a sphere is one-half of the dose rate in the infinite medium 2. Cumulated activity is derived from the whole-body retention curve and the described regular voiding schedule model 3. No attempt is made to model the physical dynamics of bladder filling and emptying
B. Snyder and Ford (12)	1. Ellipsoid with axes in ratio of 4:3:3 (left-right: front-back; top-bottom) 2. Volume range (bladder contents): 0–500 ml 3. Wall mass: 45 g 4. Wall thickness: varies geometrically according to position relative to ellipse axes, thinning with increasing bladder volume to maintain the constant 45-g mass	1. Urine volume entry rate into the bladder $U(t) = 0.69, 0.97, 1.39$ ml/min (1000, 1400, 2000 ml/day) 2. Initial bladder contents volume $V_0 = 20, 40, 60, 80\%$ of the regular void volume 3. Residual volume $V_r = 0\%, 10\%, 20\%, 30\%$ “carry-over” from regular void volume 4. Uniform activity distribution within bladder volume 5. Voiding schedule: variable; 4, 7, 10 voids/day spaced regularly	1. $R_{\beta S} = \Delta_\beta / (2\rho V(t))$ 2. $D_\gamma(V) = ae^{-cv} + be^{-dv}$ : Empirical function with coefficients a, b, c, d derived from a fit to Monte Carlo calculations as a function of volume, V	1. The variation of electron dose rate with depth was estimated using an integration of Berger's point kernel for an infinite slab of finite thickness with a semi-infinite source on one side; thus, the average electron dose in the wall was calculated as well as the surface dose 2. The empirical functions for photon dose are expressed as a function of energy at discrete intervals; thus, interpolation is required for the specific radionuclides 3. Photon dose for zero volume is calculated as for a point source
C. Diffey and Hilson (16)	1. Expanding sphere 2. Volume range (bladder contents): not specified	1. Urine volume entry rate into bladder $U(t) = 0.5-2.5$ ml/min 2. Initial bladder contents volume, $V_0 = 0$ ml 3. Residual volume $V_r = 0$ ml (complete bladder voiding assumed) 4. Uniform activity distribution within bladder contents 5. Voiding schedule: regular periods from 1 to 20 hr	1. $R_{\beta S}$ (standard assumption; however, expressed differently) 2. $X(t) = \Gamma A_V(t) g_s$ 3. $g_s = \frac{2\pi}{\mu} \left[ 1 - \frac{1 - e^{-2\mu t(t)}}{2\mu t(t)} \right]$ 4. $R_{\gamma S} = 0.96 X(t)/A(t)$	1. The photon dose rate is expressed similar to that of Model D but contains a different geometrical factor 2. Roentgen-to-rad conversion factor of 0.96 was used to convert the exposure rate to dose rate 3. The dose rate for a given interval was found by numerical integration using Simpson's rule
D. Chen et al. (4)	1. Expanding sphere 2. Volume range (bladder contents): 10–500 ml	1. Urine volume entry rate into bladder $U(t) = 1.25$ ml/min 2. Initial bladder contents volume, $V_0 = 10-500$ ml (in steps) 3. Residual volume $V_r$ was held as a fixed fraction (0.07) of the bladder volume at that voiding time 4. Uniform activity distribution within bladder contents 5. Voiding schedule: variable first voiding time, $T_1$ ; regular voiding periods of 3 hr thereafter	1. $R_{\beta S} = \Delta_\beta / (2\rho V(t))$ 2. $R_{\gamma S} = \Gamma' g_s / V(t)$ 3. $g_s = [6\pi^2 V(t)]^{1/3} = 3.9[V(t)]^{1/3}$ for $\mu t(t) \ll 1$ 4. $V(t) = \left[ \prod_{i=1}^n f_i \right] \cdot \left[ V_0 + \int_0^{T_1} U(t) dt \right] + \sum_{i=2}^n \left[ \prod_{j=1}^i f_j \right] \int_{T_{i-1}}^{T_i} U(t) dt + \int_{T_n}^t U(t) dt$ for $T_n \leq t \leq T_{n+1}$ 5. $A(t) = A_0 e^{-\lambda t} \sum_{j=1}^n \alpha_j (1 - e^{-\lambda T_j}) - \sum_{i=1}^n (1 - f_i) A(T_i) e^{-\lambda(t-T_i)}$ for $T_n \leq t \leq T_{n+1}$ 6. $D_S/A_0 = \frac{1}{A_0} \int_0^\infty \left[ \frac{3.9 \Gamma' A(t)}{[V(t)]^{2/3}} + \frac{A(t)}{2\rho V(t)} \right] dt$	1. Both the electron and photon dose rates are calculated to the inner surface of the bladder wall only

**TABLE 2**  
continued

Model	Anatomic configuration	Physiologic aspects	Calculational methods	Comments
E. Dynamic bladder model (this report)	<p>1. Expanding sphere</p> <p>2. Volume range (bladder contents): 10–770 ml</p> <p>3. Wall mass = 45 g (volume = 45 cm<sup>3</sup>)</p> <p>4. Wall thickness: Uniform thinning as bladder contents expand while maintaining a constant 45 g mass (45 cm<sup>3</sup>)</p>	<p>1. Urine volume entry rate into bladder U(t): variable corresponding to three different hydration states with the nighttime entry rate being one-half the daytime rate: 0.5 (0.25), 1.0 (0.5), 1.5 (0.75) ml · min<sup>-1</sup> (day/night)</p> <p>2. Initial bladder contents volume V<sub>0</sub>: 10–500 ml</p> <p>3. Residual volume, V<sub>r</sub>: 10 ml; fixed following each void</p> <p>4. (a) Uniform activity distribution within bladder contents            (b) Variable activity rate of entry into the bladder per specific radiopharmaceutical biological data            (c) Radiopharmaceutical administration constrained to occur at 9:00 am</p> <p>5. Voiding schedule: variable first void time T<sub>1</sub>; regular voiding period of 3 hr thereafter with the exception of the shortened period preceding the 6-hr nighttime gap (constrained to begin at 12:00 am)</p>	<p>1. Dose to the inner surface of the bladder wall is calculated similarly to the method of Model D: R<sub>BS</sub>, R<sub>S</sub>, g<sub>s</sub></p> <p>2. <math>V(t) = V_0 + \int U(t)dt; 0 \leq t \leq T_1</math> (1st void)  <math>V(t) = V_r + \int U(t)dt;</math>  <math>\text{for } T_{n-1} \leq t \leq T_n</math></p> <p>3. <math>A(t) = A_0 e^{-\lambda t} \sum_{j=1}^m \alpha_j (1 - e^{-\lambda_j t})</math>  <math>\quad - \sum_{i=1}^n \left[ 1 - \frac{V_r}{V(T_i)} \right]</math>  <math>\quad \cdot A(T_i) e^{-\lambda(t-T_i)}</math>  <math>\text{for } T_n \leq t \leq T_{n+1}</math></p> <p>4. D<sub>S</sub>/A<sub>0</sub>: same expression as for Model D</p> <p>5. Electron dose at depth into the bladder wall is calculated using an extension of the solution for point sources to spherical volume geometry:  <math>x_{50}, x_{90}</math></p>	<p>1. Electron and photon dose rates are calculated to the inner surface of the bladder wall</p> <p>2. Electron depth dose values are calculated for the x<sub>50</sub> and x<sub>90</sub> percentile distance parameters</p>

determined using a Monte Carlo technique for several discrete bladder content volumes. Photon dose for zero volume is calculated as for a point source. The bladder wall mass remains fixed at 45 g, whereas the wall thickness decreases regularly (maintaining the 4:3:3 directional ratio) as the bladder volume increases. The filling rate is assumed to be constant. The voiding schedules are uniform. The model allows for residual volumes after voiding. The radionuclide input is an exponential function of one or more components. The dose per photon emitted is given as a function of bladder volume for several discrete photon energies. These curves are fitted by two-component exponential functions, and the coefficients of the curves are provided. Total dose to the bladder wall is tabulated for intravenous injections of <sup>131</sup>I-NaI and <sup>99m</sup>Tc-pertechnetate for three filling rates, three uniform voiding schedules and four values of residual volume. Photon dose is presented separately from both surface and average electron dose. In addition, estimates are given for <sup>123</sup>I-NaI for the same filling rates and voiding schedules without consideration of residual volume. In a separate paper, Smith and Warner (15) presented the bladder dose reduction calculated from Model B for seven radionuclides. Several parameters including voiding schedule (irregular), effective half-time of the activity entering the bladder and initial urine volume at time of injection are varied.

In Model C by Diffey and Hilson (16), the bladder is taken as a sphere of variable radii. The electron dose rate to the surface of the bladder wall is derived using the same assumptions as those in Model A. The photon dose rate is derived theoretically for the spherical volume. The filling rate is assumed to be constant with uniform voiding intervals. The model does not allow for residual urine volume after voiding.

Dose was calculated only for <sup>99m</sup>Tc-DTPA with a single exponential input function assumed. The dose rate for a given interval is found by numerical integration. The electron, photon and total dose are plotted as a function of voiding interval for a fixed filling rate. In addition, total dose is plotted as a function of voiding interval for several filling rates.

Model D was developed by Chen et al. (4). The bladder is a sphere of varying radii. The electron dose rate calculations follow the standard assumptions of Model A. An analytic expression is derived for the photon dose rate to the inner surface of a sphere. The filling rate is assumed to be constant with nonuniform voiding schedules possible. The model allows for a fractional residual volume after each void. The activity input is represented by an exponential function with one or more components. Bladder wall doses for <sup>18</sup>F-FDG and <sup>99m</sup>Tc-DTPA are calculated as separate functions of voiding interval, residual urine fraction, urine production rate, or initial bladder volume with other parameters specified (i.e., fixed) within a given calculation. The authors also provide the total dose as a function of first void time after radiopharmaceutical administration for several initial volumes. As an extension of this work, Powell and Chen (17) calculated the absorbed dose as a function of depth into the bladder wall. The dose from electrons is estimated through approximation of the spherical source volume by a large number of line segment sources. The dose from each line source was estimated through integration of the point source functions of Loevinger et al. (11) or Bochkarev et al. (18). The dose from photons was estimated using the specific gamma constant for the radionuclide studied and geometrical factors from Loevinger et al. (11). The bladder wall dose for the positron emitter <sup>18</sup>F is presented along with

correlative results from thermoluminescent dosimeter phantom experiments.

Several publications not included in Table 2 are discussed briefly. Unnikrishnan (19) described a bladder model involving a sphere of variable radius. The electron dose rate at the surface of the bladder contents volume (assumed to represent the maximum dose rate) is derived from integration of Berger's scaled absorbed dose distributions (13) to represent a spherical volume source. The photon dose is taken directly from the work of Snyder and Ford (12). The urine filling rate is constant with an initially empty bladder assumed. Dose to the bladder wall is calculated for  $^{131}\text{I}$ -OIH under the assumption of activity entering the bladder either at a constant rate or instantaneously at time zero. The electron and photon dose rates are given as a function of final bladder volume for both sets of assumptions.

Dimitriou et al. (20) modified the model of Diffey and Hilson (16) for calculation of dose from  $^{99\text{m}}\text{Tc}$  cystography studies. Here, the bladder volume increases only as a result of saline flow, and all of the activity injected into the catheter is assumed to be in the bladder during the entire filling phase. Complete bladder emptying is assumed. The total dose to the bladder wall is expressed as a function of filling time for a variety of filling rates and for two different delay times between initiation of saline flow and radionuclide injection.

Cloutier et al. (7) described a dynamic bladder model that was used for calculating the dose to the fetus from activity in the mother's bladder. Dose to the bladder wall was not calculated. The ellipsoidal bladder is assumed to fill at a constant rate to 300 ml and to be displaced downward as it fills. Monte Carlo calculations are used to select time points at random from the time-activity distribution in the bladder. Because activity is assumed to enter the bladder linearly with time and the volume of the bladder contents also increases linearly with time, this Monte Carlo method weights the calculation according to both activity and bladder size. The activity in the bladder is calculated from the total-body retention function, the excretion rate through the kidney, and the time elapsed since the bladder was emptied. The model provides for voiding intervals of equal or varied time periods. The bladder is assumed to be completely emptied at each void.

Smith et al. (21) used the same geometric model and methods for calculating electron and photon dose as Snyder and Ford (12). The filling rate is taken as constant with a uniform voiding schedule. Complete emptying is assumed at each void. Radioisotope input is represented by exponential functions with one or more components. Total dose as a function of volume is calculated for 31 radionuclides and fitted with three-component exponential curves. A table of the coefficients for these curves is provided. Dose to the bladder wall is expressed as a function of bladder volume for  $^{131}\text{I}$ -OIH and  $^{99\text{m}}\text{Tc}$ -DTPA. Dose to the bladder wall is shown also as a function of bladder voiding interval for several filling rates and for initial volumes of 0 and 100 ml.

## DESCRIPTION OF THE NEW DYNAMIC BLADDER MODEL

The new model incorporates desirable features of the previous methods while introducing innovations that take into consideration some of the complexities of the dynamic situation.

### Anatomic Configuration

1. An expanding sphere model was modified from the spherical model of Chen et al. (4) that facilitated description by analytical techniques. X-ray images of a contrast-filled bladder demonstrate that the spherical approxima-

tion is appropriate for relatively large bladder volumes (4). For smaller volumes, the bladder assumes an irregular shape deviating from both the spherical model and the ellipsoidal configuration adopted in some of the previous methods (Table 2). However, as Chen et al. (4) point out, the dose to the bladder wall from nonpenetrating radiation (the major fraction of total radiation dose) is relatively independent of the actual bladder shape. Thus, the accuracy of the geometrical description at small volumes is not critical.

2. The volume range for the bladder contents was 10–770 ml. The upper bound of 770 ml results from the dynamic physiologic aspects of the model as listed below, including maximum urine entry rate, initial volume and first voiding time.
3. The wall was characterized to have uniform thinning with bladder contents expansion while maintaining a constant 45-g mass ( $45 \text{ cm}^3$ ) (9,12).

### Physiologic Aspects

1. Variable urine volume entry rates into the bladder [ $U(t)$ ] corresponded to three different hydration states, consistent with the expected normal daily urine output in the range of 1000–2000 ml: 0.5, 1.0 and 1.5 ml/min. For the 6-hr nighttime gap, the entry rate is reduced to one-half the daytime rate; i.e., 0.25, 0.5 and 0.75 ml/min, respectively.
2. There was a variable activity rate of entry into the bladder [ $A(t)$ ]. Radiopharmaceuticals were evaluated according to published biologic parameters. Table 3 contains physical and biologic data for the various radiopharmaceuticals. Administration of the radiopharmaceutical was constrained to take place at 9:00 am.
3. The initial bladder-content volume ( $V_0$ ) range was 10–500 ml.
4. The residual bladder-content volume ( $V_r$ ) was fixed at 10 ml following each void.
5. Activity was uniformly distributed within the urine.
6. The voiding schedule was as follows: first (initial) voiding time ( $T_1$ ) was variable from 20 min to 3 hr (evaluation of this parameter for minimum dose is provided for each radiopharmaceutical); 3-hr void intervals following the initial void with a shortened period leading up to midnight, depending on the time available within the 3-hr sequence pattern; and a 6-hr nighttime gap beginning at midnight.

### Calculational Methods

1. Radiation dose to the inner surface of the bladder wall was calculated using a modification of the expanding spherical model of Chen et al. (4). (Refer to Table 1 for definition of terms.)

Time-dependent bladder-content volume  $V(t)$ , with radiopharmaceutical administration taking place at time  $t = 0$ , was:

$$V(t) = V_0 + \int U(t)dt; \quad 0 \leq t < T_1 (\text{1st void}) \\ = V_r + \int U(t)dt; \quad T_{n-1} \leq t < T_n. \quad \text{Eq. 1}$$

Time-dependent bladder contents activity  $A(t)$  was:

$$A(t) = A_0 e^{-\lambda t} \sum_{j=1}^m \alpha_j (1 - e^{-\lambda_j t})$$

**TABLE 3**  
Physical and Biologic Parameters for the Radiopharmaceuticals Used in the Bladder Wall Dose Calculations

Radiopharmaceutical	Physical parameters			Biologic parameters for the bladder contents		
	$\Delta_\beta$ (mGy · kg/ MBq · sec) (36)	$\Gamma'$ (mGy · cm <sup>2</sup> / MBq · sec)	$\lambda$ (min <sup>-1</sup> )	Fraction*	Rate constant $\lambda_j$ (min <sup>-1</sup> )	Reference†
<sup>18</sup> F-FDG	$4.00 \times 10^{-5}$	$4.13 \times 10^{-4}$	$6.36 \times 10^{-3}$	0.19	$3.85 \times 10^{-2}$	22
				0.06	$1.24 \times 10^{-3}$	
<sup>99m</sup> Tc-DTPA	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.579	$1.15 \times 10^{-2}$	23
				0.421	$1.25 \times 10^{-3}$	
<sup>99m</sup> Tc-pertechnetate	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.328	$1.92 \times 10^{-3}$	24
				0.306	$4.10 \times 10^{-4}$	
<sup>99m</sup> Tc-HEDP	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	-0.0899	$5.42 \times 10^{-2}$	25
				0.720	$6.47 \times 10^{-3}$	
				0.369	$6.02 \times 10^{-4}$	
<sup>99m</sup> Tc-MDP	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	-0.115	$5.42 \times 10^{-2}$	25
				0.566	$1.06 \times 10^{-2}$	
				0.549	$5.07 \times 10^{-4}$	
<sup>99m</sup> Tc-HMPAO	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.24	$1.39 \times 10^{-3}$	26
				0.13	$2.10 \times 10^{-2}$	
<sup>99m</sup> Tc-glucoheptonate	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.35	$3.47 \times 10^{-2}$	27
				0.30	$4.81 \times 10^{-3}$	
				0.35	$1.30 \times 10^{-4}$	
<sup>99m</sup> Tc-MAG3	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.51	$3.02 \times 10^{-1}$	Wooten W. <i>personal communication</i>
				0.49	$4.05 \times 10^{-2}$	
<sup>99m</sup> Tc-HSA	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.015	$1.70 \times 10^{-3}$	28
				0.035	$3.73 \times 10^{-4}$	
				0.95	$2.48 \times 10^{-5}$	
<sup>99m</sup> Tc-RBCs	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.90	$1.93 \times 10^{-4}$	29
				0.0328	$1.92 \times 10^{-3}$	
				0.0306	$4.10 \times 10^{-4}$	
<sup>99m</sup> Tc-MIBI (rest)	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.14	$1.65 \times 10^{-3}$	30
				0.17	$4.81 \times 10^{-4}$	
<sup>99m</sup> Tc-MIBI (stress)	$2.59 \times 10^{-6}$	$5.63 \times 10^{-5}$	$1.92 \times 10^{-3}$	0.10	$1.65 \times 10^{-3}$	30
				0.20	$4.81 \times 10^{-4}$	
<sup>123</sup> I-NaI	$4.51 \times 10^{-6}$	$1.17 \times 10^{-4}$	$8.75 \times 10^{-4}$	0.729	$1.90 \times 10^{-3}$	31
				0.271	$7.41 \times 10^{-6}$	
<sup>131</sup> I-NaI	$3.04 \times 10^{-5}$	$1.61 \times 10^{-4}$	$5.99 \times 10^{-5}$	0.729	$1.90 \times 10^{-3}$	31
				0.271	$7.41 \times 10^{-6}$	
<sup>123</sup> I-OIH	$4.51 \times 10^{-6}$	$1.17 \times 10^{-4}$	$8.75 \times 10^{-4}$	0.51	$2.95 \times 10^{-1}$	32
				0.49	$4.05 \times 10^{-2}$	
<sup>124</sup> I-OIH	$3.09 \times 10^{-5}$	$3.87 \times 10^{-4}$	$1.15 \times 10^{-4}$	0.51	$2.95 \times 10^{-1}$	32
				0.49	$4.05 \times 10^{-2}$	
<sup>131</sup> I-OIH	$3.04 \times 10^{-5}$	$1.61 \times 10^{-4}$	$5.99 \times 10^{-5}$	0.51	$2.95 \times 10^{-1}$	32
				0.49	$4.05 \times 10^{-2}$	
<sup>125</sup> I-iothalamate	$3.12 \times 10^{-6}$	$1.03 \times 10^{-4}$	$8.00 \times 10^{-6}$	0.99	$6.92 \times 10^{-3}$	33
				0.01	$6.88 \times 10^{-5}$	
<sup>111</sup> In-DTPA	$5.56 \times 10^{-6}$	$2.31 \times 10^{-4}$	$1.70 \times 10^{-4}$	0.99	$6.92 \times 10^{-3}$	34
				0.01	$6.88 \times 10^{-5}$	
<sup>89</sup> Sr(SrCl)	$9.31 \times 10^{-5}$	$3.36 \times 10^{-8}$	$9.53 \times 10^{-6}$	0.18	$1.93 \times 10^{-3}$	35
				0.42	$2.41 \times 10^{-4}$	

\*For radiopharmaceuticals with excretion through the urinary tract only, the coefficients  $\alpha_j$  will be the same as those for the total body.

†Reference from which the biologic parameters were taken directly or derived through additional kinetic model analysis (the latter performed by the Radiation Internal Dose Information Center, Oak Ridge, TN).

$$= \sum_{i=1}^n [1 - V_r/V(T_i)] A(T_i) e^{-\lambda(t-T_i)}, \quad \text{Eq. 2}$$

where n is the void number (i.e., first void n = 1 and so on). The first term of Equation 2 represents the input into the bladder from the whole body. The expression after the summation sign of the second term represents the activity which leaves the bladder at void time  $T_i$ . (The second term is zero before the first void.) Thus, this second term is the sum of administered activity that has been previ-

ously voided. Physical decay for each term is included through the exponential function containing the physical decay constant.

Dose per unit administered activity to the bladder wall inner surface was:

$$\bar{D}/A_0 = (1/A_0) \int_0^\infty [3.9\Gamma' A(t)/V(t)^{2/3} + \Delta_\beta A(t)/(2\rho V(t))] dt. \quad \text{Eq. 3}$$

TABLE 4

Percentile Distance within which 50% ( $x_{50}$ ) and 90% ( $x_{90}$ ) of the Electron Energy is Absorbed in the Bladder Wall (Soft Tissue) (13)\*

For comparison, the bladder wall thickness as a function of bladder-contents volume for the new model is provided below.

Radionuclide	$x_{50}$ (cm)	$x_{90}$ (cm)
<sup>18</sup> F	0.038	0.0939
<sup>99m</sup> Tc	0.0090	0.0148
<sup>123</sup> I	0.0093	0.0166
<sup>124</sup> I	0.182	0.431
<sup>131</sup> I	0.0285	0.0822

\*Values for <sup>18</sup>F, <sup>124</sup>I, and <sup>131</sup>I are taken directly from reference 13. Values for <sup>99m</sup>Tc and <sup>123</sup>I are derived from results of Reference 13 for monoenergetic electrons and known abundances of the emissions of these nuclides.

	Bladder contents volume (cm <sup>3</sup> )				
	50	100	300	500	800
Bladder wall thickness (cm <sup>1</sup> )	0.55	0.38	0.20	0.14	0.11

<sup>1</sup>Spherical-shell bladder-wall volume remains constant at 45 cm<sup>3</sup>.

Considerations leading to this analytic expression as derived by Chen et al. (4) were described earlier in the text and in Table 2 as Model D. The calculations as performed by numerical integration were terminated when the ratio of the dose in a given interval between voids to the total dose including that interval was < 0.001%, i.e.,  $D(n \rightarrow n+1)/D(1 \rightarrow n+1) \leq 10^{-5}$ .

Comparison of the Absorbed Dose per Unit Administered Activity at the Bladder Wall Surface for the Various Models for Selected Radiopharmaceuticals

Radionuclide	Initial volume $V_0$ (ml)	Bladder model									
		Model A MIRD 5 (Revised) (5)		Model B Snyder and Ford (12)		Model C Diffey and Hilson (16)		Model D Chen et al. (4)			
		$T_{1m}^*$ (min)	$\bar{D}/A_0$ (mGy/MBq)	$T_{1m}^*$ (min)	$\bar{D}/A_0$ (mGy/MBq)	$T_{1m}^*$ (min)	$\bar{D}/A_0$ (mGy/MBq)	$T_{1m}^*$ (min)	$\bar{D}/A_0$ (mGy/MBq)		
<sup>18</sup> F-FDG	10	—	—	40	0.22	40	0.20	40	0.23	40	0.31
	200	40	0.059	60	0.081	80	0.065	60-80	0.084	80	0.091
	500	—	—	80	0.049	100	0.038	80-100	0.051	100	0.053
<sup>99m</sup> Tc-DTPA	10	—	—	60-80	0.076	60-80	0.077	60-80	0.083	80	0.099
	200	60	0.029	120-140	0.048	140	0.045	120-140	0.050	160	0.055
	500	—	—	140-180	0.035	160-180	0.033	160-180	0.037	180+	0.041
<sup>99m</sup> Tc-MAG3	10	—	—	20	0.11	20	0.12	20	0.12	40	0.19
	200	20	0.032	40	0.046	40-60	0.046	40	0.049	60	0.051
	500	—	—	60	0.030	40-80	0.030	60	0.032	60	0.030
<sup>131</sup> I-NaI	10	—	—	180+	0.81	180+	0.81	180+	0.86	120	0.93
	200	180+	0.46	180+	0.78	180+	0.78	180+	0.84	180+	0.78
	500	—	—	180+	0.76	180+	0.76	180+	0.81	180+	0.74
<sup>123</sup> I-OIH	10	—	—	20	0.18	20	0.18	20	0.25	40	0.38
	200	20-40	0.065	40	0.073	40-60	0.070	40	0.10	60	0.10
	500	—	—	60	0.046	60	0.043	60	0.068	60	0.061
<sup>124</sup> I-OIH	10	—	—	20	1.20	20	1.30	20	1.40	40	2.15
	200	20-40	0.43	40-60	0.49	40-60	0.49	40	0.57	60	0.56
	500	—	—	60	0.30	60	0.30	40-80	0.41	80	0.32
<sup>131</sup> I-OIH	10	—	—	20	1.00	20	1.02	20	1.20	40	1.82
	200	20-40	0.30	60	0.35	60	0.35	40-60	0.43	60	0.45
	500	—	—	60	0.22	60	0.22	60-80	0.27	80	0.25

\* $T_{1m}$  represents the initial (first) void time which provides minimum dose for the given initial volume  $V_0$ .

Explanatory points for  $T_{1m}$ : (a) a value of 40-80 indicates that the same minimum dose value as shown in the adjacent column was obtained for initial void times of 40, 60, 80 min; (b) a value of 140-180 indicates that the same minimum dose value was obtained for initial void times from 140 out to 180 min; and (c) a value of 180+ indicates that the minimum dose value calculated occurred at the 180-min void point and is that value shown in the adjacent column. The actual dose minimum may occur at longer initial void times.

2. Electron dose at depth into the bladder wall was determined as follows. Depth dose characteristics for point sources or discrete distributions of radionuclides may be described through use of the percentile distance parameter, which denotes the fraction of emitted energy absorbed in a sphere of radius  $x$  around the source. Thus,  $x_{90}$  and  $x_{50}$  specify the distance from the source within which 90% and 50%, respectively, of the energy is absorbed. The values of these parameters, as given by Berger (13), for some of the radionuclides evaluated in this report, are given in Table 4. For beta emitters, the values are taken directly from a previous report (13). For nuclides with a series of electron emissions, the percentile distance values are determined through consideration of the energies and abundances of the various emissions and the values given (13) for the individual energies. Formulas for extension of these solutions for point sources to the spherical volume source geometry assumed for the bladder are taken from a previous report (14). Bladder size is determined at each time step by solution of the time-dependent bladder-content volume expression (Eq. 1) using the optimal first void time (as determined by average bladder-wall dose) and three different values of initial volume. Integration of the final expression is accomplished by use of the trapezoidal integration method.

## RESULTS

A variety of commonly used radiopharmaceuticals was studied to provide a comparison among bladder wall dosimetry models and to evaluate the new model. These include: <sup>18</sup>F-FDG

**TABLE 6**  
Electron Depth: Dose per Unit Administered Activity to the Bladder Wall at the Surface,  $x_{50}$  and  $x_{90}$

Radiopharmaceutical	Initial volume $V_0$ (mL)	Bladder fill rate $U(t)$ (mL/min)	Time of first void $T_1$ (min)	Absorbed dose/administered activity (mGy/MBq)		
				Surface	At $x_{50}$	At $x_{90}$
$^{18}\text{F}$ -FDG	10	0.5	40	4.4E-01	8.7E-02	7.3E-03
	10	1.0	40	2.5E-01	4.8E-02	4.1E-03
	10	1.5	40	1.7E-01	3.4E-02	2.9E-03
	200	0.5	80	8.6E-02	1.7E-02	1.5E-03
	200	1.0	80	6.3E-02	1.3E-02	1.1E-03
	200	1.5	80	5.3E-02	1.1E-02	9.1E-04
	500	0.5	100	4.5E-02	9.2E-03	7.8E-04
	500	1.0	100	3.5E-02	7.0E-03	6.0E-04
	500	1.5	100	3.0E-02	6.0E-03	5.1E-04
$^{99\text{m}}$ Tc-DTPA	10	0.5	80	1.1E-01	1.8E-02	1.4E-03
	10	1.0	80	5.9E-02	9.1E-03	7.1E-04
	10	1.5	80	4.0E-02	6.1E-03	4.8E-04
	200	0.5	160	4.6E-02	1.6E-02	1.2E-03
	200	1.0	160	2.9E-02	8.1E-03	6.3E-04
	200	1.5	160	2.2E-02	5.4E-03	4.2E-04
	500	0.5	180	3.3E-02	5.0E-03	3.9E-04
	500	1.0	180	2.1E-02	3.1E-03	2.4E-04
	500	1.5	180	1.6E-02	2.3E-03	1.8E-04
$^{99\text{m}}$ Tc-pertechnetate	10	0.5	100	3.4E-02	5.7E-03	4.6E-04
	10	1.0	100	1.8E-02	3.0E-03	2.2E-04
	10	1.5	100	1.2E-02	1.9E-03	1.5E-04
	200	0.5	180	2.2E-02	3.2E-03	2.6E-04
	200	1.0	180	1.2E-02	1.9E-03	1.5E-04
	200	1.5	180	8.8E-03	1.3E-03	1.0E-04
	500	0.5	180	2.0E-02	3.0E-03	2.4E-04
	500	1.0	180	1.1E-02	1.7E-03	1.3E-04
	500	1.5	180	7.8E-03	1.2E-03	9.2E-05
$^{99\text{m}}$ Tc-HEDP	10	0.5	120	8.4E-02	2.7E-02	2.2E-03
	10	1.0	120	4.3E-02	1.5E-02	1.2E-03
	10	1.5	120	2.9E-02	1.1E-02	8.4E-04
	200	0.5	180	4.3E-02	1.7E-02	1.4E-03
	200	1.0	180	2.6E-02	1.1E-02	8.6E-04
	200	1.5	180	1.9E-02	8.1E-03	6.5E-04
	500	0.5	180	3.6E-02	1.6E-02	1.3E-03
	500	1.0	180	2.1E-02	1.0E-02	7.8E-04
	500	1.5	180	1.5E-02	7.6E-03	5.9E-04
$^{99\text{m}}$ Tc-MDP	10	0.5	120	7.5E-02	3.0E-02	2.3E-03
	10	1.0	120	3.8E-02	1.7E-02	1.3E-03
	10	1.5	120	2.6E-02	1.2E-02	9.5E-04
	200	0.5	180	3.5E-02	1.9E-02	1.5E-03
	200	1.0	180	2.1E-02	1.2E-02	9.6E-04
	200	1.5	180	1.6E-02	9.3E-03	7.3E-04
	500	0.5	180	2.7E-02	1.8E-02	1.4E-03
	500	1.0	180	1.6E-02	1.1E-02	8.9E-04
	500	1.5	180	1.2E-02	8.7E-03	6.8E-04
$^{99\text{m}}$ Tc-HMPAO	10	0.5	80	3.8E-02	5.9E-03	4.6E-04
	10	1.0	80	2.0E-02	3.0E-03	2.4E-04
	10	1.5	80	1.4E-02	2.1E-03	1.6E-04
	200	0.5	120	1.7E-02	3.8E-03	3.0E-04
	200	1.0	120	1.0E-02	1.9E-03	1.5E-04
	200	1.5	120	7.6E-03	1.3E-03	1.1E-04
	500	0.5	180	1.3E-02	1.9E-03	1.5E-04
	500	1.0	180	7.5E-03	1.1E-03	8.9E-05
	500	1.5	180	5.7E-03	8.4E-04	6.5E-05
$^{99\text{m}}$ Tc-glucoheptonate	10	0.5	60	1.1E-01	1.6E-02	1.2E-03
	10	1.0	60	5.5E-02	8.2E-03	6.4E-04
	10	1.5	60	3.8E-02	5.6E-03	4.3E-04
	200	0.5	100	3.8E-02	7.3E-03	5.7E-04
	200	1.0	100	2.3E-02	4.0E-03	3.1E-04
	200	1.5	100	1.8E-02	2.9E-03	2.3E-04
	500	0.5	140	2.5E-02	8.0E-03	6.3E-04
	500	1.0	140	1.6E-02	4.0E-03	3.1E-04
	500	1.5	140	1.2E-02	2.7E-03	2.1E-04

**TABLE 6**  
Continued

Initial	Bladder fill rate	Time of	Absorbed dose/administered activity (mGy/MBq)
for dose to the bladder wall that are, in general, slightly less than those given by the new model.			
Each radiopharmaceutical has a unique time-activity curve for bladder activity. This variability, when combined with a nonuniform voiding schedule and analyzed in terms of initial bladder volume and first bladder voiding time, may be used to predict the optimum first voiding time and most desirable hydration states. Large initial bladder volumes and higher rates of urine flow into the bladder result in lower total bladder wall dose. Earlier first voiding times do not necessarily result in lower total bladder wall doses. In fact, the results indicate that the optimum first voiding time is from 40 min to 3 hr after administration, depending on the radiopharmaceutical. The optimum first void time ( $T_{1m}$ ) does not appear to be sensitive to the model used.			
Electron dose decreases rapidly with increasing depth in the wall at a gradient determined by the electron energy spectrum. For most nuclear medicine radiopharmaceuticals, 90% of the energy is deposited within 0.1 cm of the bladder interior wall surface. An exception is $^{124}\text{I}$ , potentially a contaminant in $^{123}\text{I}$ . Other high-energy beta emitters such as $^{90}\text{Y}$ or other therapy agents, however, might contribute a significant dose deep into the bladder wall and possibly even into surrounding tissues.			
<b>ACKNOWLEDGMENTS</b>			
We gratefully acknowledge the assistance of William S. Kassing in preparing the figures and tables for this revised Pamphlet.			
<b>REFERENCES</b>			
1. Thomas SR, Stabin MG, Chen C-T, Samarutunga RC. MIRD Pamphlet No. 14: a Dynamic Urinary Bladder Model for Radiation Dose, Calculations. <i>J Nucl Med</i> 1992;33:783-802. 2. [Erratum]. <i>J Nucl Med</i> 1994;35:73. 3. Dowd MT, Chen C-T, Wendel MJ, Faulhaber PJ, Cooper MD. Radiation dose to the bladder wall from $2\text{-}^{18}\text{F}$ fluoro-2-deoxy-D-glucose in adult humans. <i>J Nucl Med</i> 1991;32:707-712. 4. Chen C-T, Harper PV, Lathrop KA. A simple dynamic model for calculating radiation absorbed dose to the bladder wall. In: Schlaefke-Stelson AT, Watson EE, eds. <i>Fourth International Radiopharmaceutical Dosimetry Symposium</i> , Nov. 5-8, 1985, Oak Ridge, TN: CONF-851113-(DE86010102), 587-612. 5. Snyder WS, Ford MR, Warner GG. MIRD Pamphlet No. 5 (Revised): estimates of specific absorbed fractions for photon sources uniformly distributed in various organs of heterogeneous phantom. New York: The Society of Nuclear Medicine; 1978. 6. Cristy M, Eckerman KF. <i>Specific absorbed fractions of energy at various ages from internal photon sources. I. Methods</i> , ORNL Publ. No. TM-8381/V1. 1987. 7. Cloutier RJ, Smith SA, Watson EE, et al. Dose to the fetus from radionuclides in the bladder. <i>Health Phys</i> 1973;25:147-161. 8. Loevinger R, Budinger TF, Watson EE. MIRD primer for absorbed dose calculations. New York: The Society of Nuclear Medicine; 1988. 9. Snyder WS, Ford MR, Warner GG, Watson SB. MIRD Pamphlet No. 11: "S," absorbed dose per unit cumulated activity for selected radionuclides and organs. New York: The Society of Nuclear Medicine; 1975. 10. Snyder WS, Ford MR, Warner GG, Watson SB. A tabulation of dose equivalent per microcurie-day for source and target organs of an adult for various radionuclides. ORNL 5000. Oak Ridge TN: Oak Ridge National Laboratory; 1975. 11. Loevinger R, Japha EM, Brownell GL. Discrete radioisotope sources. In: Hine GI, Brownell GL, eds. <i>Radiation dosimetry</i> . New York: Academic Press; 1956:693-799. 12. Snyder WS, Ford MR. Estimation of dose to the urinary bladder and to the gonads. In: Cloutier RJ, Coffey JL, Snyder WS, Watson EE, eds. <i>Radiopharmaceutical dosimetry symposium</i> , HEW Publication (FDA) 76-8044, 1976. Oak Ridge, TN, April 26-29, 1976. 313-350. 13. Berger MJ. MIRD Pamphlet No. 7: distribution of absorbed dose around point sources of electrons and beta particles in water and other media. <i>J Nucl Med</i> 1971;12(suppl 5).	14. Berger MJ. Beta-ray dosimetry calculations with the use of point kernels in medical radionuclides, radiation dose and effects. AEC Symposium Series No. 20. USAEC Division of Technical Information, 1970. 15. Smith EM, Warner GG. Practical methods of dose reduction to the bladder wall. In: <i>Radiopharmaceutical dosimetry symposium</i> . Oak Ridge, TN, April 26-29, 1976. 351-359. 16. Difley B, Hilson A. Absorbed dose to the bladder form. $^{99m}\text{Tc}$ -DTPA [Letter]. <i>Br J Radiol</i> 1976;49:196-198. 17. Powell GR, Chen C-T. Radiation absorbed dose to bladder walls from positron emitters in the bladder content. <i>Med Phys</i> 1987;14:1079-1086. 18. Bochkarev VV, Radzievsky GB, Timofeev LV, Demiano DA. Distribution and absorbed energy from a point beta-source in a tissue equivalent medium. <i>Int J Appl Radiat Isot</i> 1972;23:493. 19. Unnikrishnan K. Dose to the urinary bladder from radionuclides in urine. <i>Phys Med Biol</i> 1974;19:329-340. 20. Dimitriou P, Fretzayas A, Nicolaoudou P, et al. Estimates of dose to the bladder during direct radionuclide cystography: concise communication. <i>J Nucl Med</i> 1984;25:792-795. 21. Smith T, Veall N, Wotton R. Bladder wall dose from administered radiopharmaceuticals: the effects of variations in urine flow rate, voiding interval, and initial bladder content. <i>Radiat Prot Dosim</i> 1982;2:183-189. 22. Jones S, Alavi A, Christman D, Montanez I, Wolf A, Reivich M. The radiation dosimetry of $2\text{-}^{18}\text{F}$ fluoro-2-deoxy-D-glucose in man. <i>J Nucl Med</i> 1982;23:613-617. 23. Thomas SR, Atkins HL, McAfee JG, et al. MIRD Dose Estimate Report No. 12: radiation absorbed dose from $\text{Tc-99m}$ diethylenetriaminepentacetic acid (DTPA). <i>J Nucl Med</i> 1984;25:503-505. 24. Lathrop KA, Atkins HL, Berman M, et al. Summary of current radiation dose estimates to normal humans from $\text{Tc-99m}$ as sodium pertechnetate. <i>J Nucl Med</i> 1976;17:74-77. 25. Weber DA, Makler PT Jr, Watson EE, et al. Radiation absorbed dose from technetium-99-labeled bone imaging agents. <i>J Nucl Med</i> 1989;30:1117-1122. 26. Soundy RG, Tyrell DA, Pickett RD, Stabin MG. The radiation dosimetry of $\text{Tc-99m}$ exametazime. <i>Nucl Med Commun</i> 1990;11:791-799. 27. Radiation dose to patients from radiopharmaceuticals (technetium-gluconate, glucoheptone). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:193-194. 28. Radiation dose to patients from radiopharmaceuticals (technetium-labelled albumin (HSA)). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:173. 29. Radiation dose to patients from radiopharmaceuticals (technetium-labelled erythrocytes). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:209-210. 30. Radiation dose to patients from radiopharmaceuticals (technetium-labelled MIBI). In: ICRP Publication No. 62: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Tarrytown, NY: Pergamon Press, Inc.; 1993: 21-24. 31. Berman M, Braverman LE, Burke J, et al. Summary of current radiation dose estimates to humans from $\text{I-123}$ , $\text{I-124}$ , $\text{I-125}$ , $\text{I-126}$ , $\text{I-130}$ , $\text{I-131}$ , and $\text{I-132}$ as sodium iodide. <i>J Nucl Med</i> 1975;16:857-860. 32. Lindmo T, Skerettting A, Nakken K. An examination of different mathematical models for renal function as measured by $^{131}\text{I}$ -hippuran renography. <i>Med Phys</i> 1974;1:193-197. 33. Radiation dose to patients from radiopharmaceuticals (iothalamate). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:315-316. 34. Radiation dose to patients from radiopharmaceuticals (indium-DTPA). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:237-240. 35. Radiation dose to patients from radiopharmaceuticals (strontium). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:169-171. 36. Weber DA, Eckerman KF, Dillman LT, et al. <i>MIRD: radionuclide data and decay schemes</i> . New York: The Society of Nuclear Medicine; 1989.		

## APPENDIX A

DTPA calculations for the various models are shown in Figures A1-A4 and Tables A1-A4. Calculations for the new model are shown in Figures A5-A24 and Tables A5-A24.

**TABLE 6**  
Electron Depth: Dose per Unit Administered Activity to the Bladder Wall at the Surface,  $x_{50}$  and  $x_{90}$

Radiopharmaceutical	Initial volume $V_0$ (ml)	Bladder fill rate $U(t)$ (mL/min)	Time of first void $T_1$ (min)	Absorbed dose/administered activity (mGy/MBq)		
				Surface	At $x_{50}$	At $x_{90}$
$^{18}\text{F}$ -FDG	10	0.5	40	4.4E-01	8.7E-02	7.3E-03
	10	1.0	40	2.5E-01	4.8E-02	4.1E-03
	10	1.5	40	1.7E-01	3.4E-02	2.9E-03
	200	0.5	80	8.6E-02	1.7E-02	1.5E-03
	200	1.0	80	6.3E-02	1.3E-02	1.1E-03
	200	1.5	80	5.3E-02	1.1E-02	9.1E-04
	500	0.5	100	4.5E-02	9.2E-03	7.8E-04
	500	1.0	100	3.5E-02	7.0E-03	6.0E-04
	500	1.5	100	3.0E-02	6.0E-03	5.1E-04
	500	1.5	100	3.0E-02	6.0E-03	5.1E-04
$^{99\text{m}}$ Tc-DTPA	10	0.5	80	1.1E-01	1.8E-02	1.4E-03
	10	1.0	80	5.9E-02	9.1E-03	7.1E-04
	10	1.5	80	4.0E-02	6.1E-03	4.8E-04
	200	0.5	160	4.6E-02	1.6E-02	1.2E-03
	200	1.0	160	2.9E-02	8.1E-03	6.3E-04
	200	1.5	160	2.2E-02	5.4E-03	4.2E-04
	500	0.5	180	3.3E-02	5.0E-03	3.9E-04
	500	1.0	180	2.1E-02	3.1E-03	2.4E-04
	500	1.5	180	1.6E-02	2.3E-03	1.8E-04
	500	1.5	180	1.6E-02	2.3E-03	1.8E-04
$^{99\text{m}}$ Tc-pertechnetate	10	0.5	100	3.4E-02	5.7E-03	4.6E-04
	10	1.0	100	1.8E-02	3.0E-03	2.2E-04
	10	1.5	100	1.2E-02	1.9E-03	1.5E-04
	200	0.5	180	2.2E-02	3.2E-03	2.6E-04
	200	1.0	180	1.2E-02	1.9E-03	1.5E-04
	200	1.5	180	8.8E-03	1.3E-03	1.0E-04
	500	0.5	180	2.0E-02	3.0E-03	2.4E-04
	500	1.0	180	1.1E-02	1.7E-03	1.3E-04
	500	1.5	180	7.8E-03	1.2E-03	9.2E-05
	500	1.5	180	7.8E-03	1.2E-03	9.2E-05
$^{99\text{m}}$ Tc-HEDP	10	0.5	120	8.4E-02	2.7E-02	2.2E-03
	10	1.0	120	4.3E-02	1.5E-02	1.2E-03
	10	1.5	120	2.9E-02	1.1E-02	8.4E-04
	200	0.5	180	4.3E-02	1.7E-02	1.4E-03
	200	1.0	180	2.6E-02	1.1E-02	8.6E-04
	200	1.5	180	1.9E-02	8.1E-03	6.5E-04
	500	0.5	180	3.6E-02	1.6E-02	1.3E-03
	500	1.0	180	2.1E-02	1.0E-02	7.8E-04
	500	1.5	180	1.5E-02	7.6E-03	5.9E-04
	500	1.5	180	1.5E-02	7.6E-03	5.9E-04
$^{99\text{m}}$ Tc-MDP	10	0.5	120	7.5E-02	3.0E-02	2.3E-03
	10	1.0	120	3.8E-02	1.7E-02	1.3E-03
	10	1.5	120	2.6E-02	1.2E-02	9.5E-04
	200	0.5	180	3.5E-02	1.9E-02	1.5E-03
	200	1.0	180	2.1E-02	1.2E-02	9.6E-04
	200	1.5	180	1.6E-02	9.3E-03	7.3E-04
	500	0.5	180	2.7E-02	1.8E-02	1.4E-03
	500	1.0	180	1.6E-02	1.1E-02	8.9E-04
	500	1.5	180	1.2E-02	8.7E-03	6.8E-04
	500	1.5	180	1.2E-02	8.7E-03	6.8E-04
$^{99\text{m}}$ Tc-HMPAO	10	0.5	80	3.8E-02	5.9E-03	4.6E-04
	10	1.0	80	2.0E-02	3.0E-03	2.4E-04
	10	1.5	80	1.4E-02	2.1E-03	1.6E-04
	200	0.5	120	1.7E-02	3.8E-03	3.0E-04
	200	1.0	120	1.0E-02	1.9E-03	1.5E-04
	200	1.5	120	7.6E-03	1.3E-03	1.1E-04
	500	0.5	180	1.3E-02	1.9E-03	1.5E-04
	500	1.0	180	7.5E-03	1.1E-03	8.9E-05
	500	1.5	180	5.7E-03	8.4E-04	6.5E-05
	500	1.5	180	5.7E-03	8.4E-04	6.5E-05
$^{99\text{m}}$ Tc-glucoheptonate	10	0.5	60	1.1E-01	1.6E-02	1.2E-03
	10	1.0	60	5.5E-02	8.2E-03	6.4E-04
	10	1.5	60	3.8E-02	5.6E-03	4.3E-04
	200	0.5	100	3.8E-02	7.3E-03	5.7E-04
	200	1.0	100	2.3E-02	4.0E-03	3.1E-04
	200	1.5	100	1.8E-02	2.9E-03	2.3E-04
	500	0.5	140	2.5E-02	8.0E-03	6.3E-04
	500	1.0	140	1.6E-02	4.0E-03	3.1E-04
	500	1.5	140	1.2E-02	2.7E-03	2.1E-04

**TABLE 6**  
Continued

Radiopharmaceutical	Initial volume V <sub>0</sub> (ml)	Bladder fill rate U(t) (ml/min)	Time of first void T <sub>1</sub> (min)	Absorbed dose/administered activity (mGy/MBq)		
				Surface	At x <sub>50</sub>	At x <sub>90</sub>
<sup>99m</sup> Tc-MAG	10	0.5	40	2.3E-01	3.2E-02	2.5E-03
	10	1.0	40	1.2E-01	1.8E-02	1.4E-03
	10	1.5	40	8.7E-02	1.2E-02	9.7E-04
	200	0.5	60	3.8E-02	7.3E-03	5.7E-04
	200	1.0	60	2.7E-02	4.6E-03	3.5E-04
	200	1.5	60	2.3E-02	3.4E-03	2.7E-04
	500	0.5	60	2.2E-02	4.5E-03	3.5E-04
	500	1.0	60	1.5E-02	2.6E-03	2.0E-04
	500	1.5	60	1.2E-02	2.0E-03	1.6E-04
<sup>99m</sup> Tc-HSA	10	0.5	120	3.8E-03	7.0E-04	5.4E-05
	10	1.0	120	2.0E-03	3.2E-04	2.7E-05
	10	1.5	120	1.4E-03	2.3E-04	1.8E-05
	200	0.5	180	2.9E-03	4.3E-04	3.5E-05
	200	1.0	180	1.6E-03	2.4E-04	1.9E-05
	200	1.5	180	1.1E-03	1.7E-04	1.3E-05
	500	0.5	180	2.7E-03	4.3E-04	3.2E-05
	500	1.0	180	1.4E-03	2.2E-04	1.7E-05
	500	1.5	180	1.0E-03	1.5E-04	1.2E-05
<sup>99m</sup> Tc-RBCs	10	0.5	100	1.6E-02	2.7E-03	2.2E-04
	10	1.0	100	8.3E-03	1.4E-03	1.1E-04
	10	1.5	100	5.6E-03	9.2E-04	7.0E-05
	200	0.5	180	1.2E-02	1.9E-03	1.5E-04
	200	1.0	180	6.5E-03	1.0E-03	7.8E-05
	200	1.5	180	4.6E-03	7.0E-04	5.4E-05
	500	0.5	180	1.1E-02	1.8E-03	1.4E-04
	500	1.0	180	6.1E-03	9.5E-04	7.3E-05
	500	1.5	180	4.2E-03	6.5E-04	5.1E-05
<sup>99m</sup> Tc-MIBI (rest)	10	0.5	100	1.5E-02	2.6E-03	2.1E-04
	10	1.0	100	7.9E-03	1.3E-03	1.0E-04
	10	1.5	100	5.4E-03	8.6E-04	6.8E-05
	200	0.5	180	1.0E-02	1.6E-03	1.2E-04
	200	1.0	180	5.8E-03	8.6E-04	6.8E-05
	200	1.5	180	4.1E-03	6.2E-04	4.9E-05
	500	0.5	180	9.6E-03	1.5E-03	1.2E-04
	500	1.0	180	5.2E-03	7.8E-04	6.2E-05
	500	1.5	180	3.6E-03	5.4E-04	4.3E-05
<sup>99m</sup> Tc-MIBI (stress)	10	0.5	100	1.3E-02	2.3E-03	1.8E-04
	10	1.0	100	6.9E-03	1.1E-03	1.0E-04
	10	1.5	100	4.7E-03	7.6E-04	5.9E-05
	200	0.5	180	9.2E-03	1.4E-03	1.1E-04
	200	1.0	180	5.1E-03	7.8E-04	5.9E-05
	200	1.5	180	3.6E-03	5.4E-04	4.3E-05
	500	0.5	180	8.5E-03	1.3E-03	1.0E-04
	500	1.0	180	4.6E-03	7.0E-04	5.4E-05
	500	1.5	180	3.2E-03	4.9E-04	3.8E-05
<sup>123</sup> I-NaI	10	0.5	100	1.5E-01	3.1E-02	2.7E-03
	10	1.0	100	7.5E-02	1.5E-02	1.3E-03
	10	1.5	100	5.0E-02	9.5E-03	8.6E-04
	200	0.5	180	1.1E-01	1.8E-02	1.6E-03
	200	1.0	180	5.7E-02	9.5E-03	8.6E-04
	200	1.5	180	4.0E-02	6.8E-03	5.9E-04
	500	0.5	180	9.8E-02	1.7E-02	1.5E-03
	500	1.0	180	5.2E-02	8.9E-03	7.8E-04
	500	1.5	180	3.6E-02	6.2E-03	5.4E-04
<sup>131</sup> I-NaI	10	0.5	120	1.6E-00	3.0E-01	2.4E-02
	10	1.0	120	7.9E-01	1.5E-01	1.2E-02
	10	1.5	120	5.3E-01	1.0E-01	8.1E-03
	200	0.5	180	1.3E-00	3.0E-01	2.4E-02
	200	1.0	180	6.6E-01	1.6E-01	1.2E-02
	200	1.5	180	4.5E-01	1.1E-01	8.6E-03
	500	0.5	180	1.2E-00	3.0E-01	2.3E-02
	500	1.0	180	6.2E-01	1.5E-01	1.2E-02
	500	1.5	180	4.3E-01	1.0E-01	8.1E-03

**TABLE 6**  
Continued

Radiopharmaceutical	Initial volume $V_0$ (ml)	Bladder fill rate $U(t)$ (ml/min)	Time of first void $T_1$ (min)	Absorbed dose/administered activity (mGy/MBq)		
				Surface	At $x_{50}$	At $x_{90}$
$^{123}\text{I-OIH}$	10	0.5	40	4.2E-01	6.5E-02	5.7E-03
	10	1.0	40	2.3E-01	3.5E-02	3.2E-03
	10	1.5	40	1.6E-01	2.5E-02	2.2E-03
	200	0.5	60	7.3E-02	1.2E-02	1.1E-03
	200	1.0	60	5.1E-02	8.1E-03	7.3E-04
	200	1.5	60	4.2E-02	6.6E-03	5.9E-04
	500	0.5	60	4.2E-02	7.3E-03	6.5E-04
	500	1.0	60	2.9E-02	4.6E-03	4.1E-04
	500	1.5	60	2.3E-02	3.7E-03	3.2E-04
	10	0.5	40	3.1E-00	4.6E-01	2.0E-02
$^{124}\text{I-OIH}$	10	1.0	40	1.6E-00	2.5E-01	1.1E-02
	10	1.5	40	1.1E-00	1.7E-01	7.6E-03
	200	0.5	60	5.4E-01	8.9E-02	4.0E-03
	200	1.0	60	3.7E-01	6.0E-02	2.7E-03
	200	1.5	60	3.0E-01	4.9E-02	2.2E-03
	500	0.5	80	2.7E-01	4.9E-02	2.2E-03
	500	1.0	80	2.0E-01	3.2E-02	1.5E-03
	500	1.5	80	1.7E-01	2.7E-02	1.3E-03
	10	0.5	40	3.0E-00	6.5E-01	5.1E-02
	10	1.0	40	1.6E-00	3.5E-01	2.7E-02
$^{131}\text{I-OIH}$	10	1.5	40	1.1E-00	2.4E-01	1.9E-02
	200	0.5	60	5.4E-01	1.2E-01	1.0E-02
	200	1.0	60	3.7E-01	8.4E-02	6.5E-03
	200	1.5	60	3.0E-01	6.8E-02	5.4E-03
	500	0.5	80	2.7E-01	6.8E-02	5.4E-03
	500	1.0	80	2.0E-01	4.3E-02	3.5E-03
	500	1.5	80	1.7E-01	3.8E-02	3.0E-03

(22),  $^{99\text{m}}\text{Tc-DTPA}$  (23),  $^{99\text{m}}\text{Tc}$ -pertechnetate (24),  $^{99\text{m}}\text{Tc}$ -HEDP (25),  $^{99\text{m}}\text{Tc-MDP}$  (25),  $^{99\text{m}}\text{Tc-HMPAO}$  (26),  $^{99\text{m}}\text{Tc}$ -glucoheptonate (27),  $^{99\text{m}}\text{Tc-MAG3}$  (Wooten W, St. Agnes Medical Center, Fresno, CA, *personal communication*),  $^{99\text{m}}\text{Tc}$ -HSA (28),  $^{99\text{m}}\text{Tc-RBCs}$  (29),  $^{99\text{m}}\text{Tc}$ -sestamibi (rest and stress) (30),  $^{123}\text{I-NaI}$  (31),  $^{131}\text{I-NaI}$  (31),  $^{123}\text{I-OIH}$  (32),  $^{124}\text{I-OIH}$  (32),  $^{131}\text{I-OIH}$  (32),  $^{125}\text{I}$ -iothalamate (33),  $^{111}\text{In-DTPA}$  (34) and  $^{89}\text{Sr-SrCl}$  (35). The biological parameters for these radiopharmaceuticals were taken or derived from the references cited (Table 3).

The radiation absorbed dose per unit administered activity  $\bar{D}/A_0$  to the inner bladder wall surface was calculated for each radiopharmaceutical as a function of initial bladder contents volume ( $V_0$ ) and first void time ( $T_1$ ). As a function of these parameters, families of dose curves as well as tabular data were generated for each model. For the previously published models (Table 2), 3-hr voiding intervals were assumed after the variable first void time. In the Appendix, Figures A1–A4 provide examples of the  $^{99\text{m}}\text{Tc-DTPA}$  results for these models with the calculations presented in Tables A1–A4.

Similar calculations for the new model are shown in Figures A5–A24 and are presented in Tables A5–A24. For the figures, only the results for a bladder urine input function  $U(t) = 1.0/0.5$  ml/min (day/night) are shown. The tables provide data for the other entry rates evaluated (i.e., 0.5/0.25 and 1.5/0.75 ml/min). Examples of the bladder activity curves for two radiopharmaceuticals are shown in Figures A25 and A26 for  $U(t) = 1.0/0.5$  ml/min,  $V_0 = 100$  ml and  $T_1 = 60$  min.

A comparison of the absorbed dose per unit administered activity at the bladder wall inner surface is contained in Table 5 for all models for selected radiopharmaceuticals. Values are

given for the initial void time which results in minimum dose ( $T_{1m}$ ) for the initial bladder volume specified.

Table 6 provides the electron absorbed dose per unit administered activity at the bladder wall surface and at the distances  $x_{50}$  and  $x_{90}$  as calculated by the new model for selected radiopharmaceuticals for three different  $V_0$  and  $U(t)$  values. The first void times represent the optimal first void time ( $T_{1m}$  as determined by the surface dose evaluation) or a value close to that. Figures A27 and A28 show examples of the electron dose per unit administered activity as a function of distance into the bladder wall for  $^{18}\text{F}$  FDG and  $^{99\text{m}}\text{Tc-DTPA}$  under selected conditions.

## DISCUSSION AND CONCLUSION

The published models for urinary bladder wall dose have provided a useful framework for development of the new comprehensive dynamic bladder model. Provisions for an expanding/contracting bladder with variable initial volume, first void time and rate of urine entry, along with options for residual volume allow a more detailed understanding of bladder wall dosimetry than offered by the MIRD 5 (Revised) model.

Inspection of the comparative results in Table 5 for selected radiopharmaceuticals indicates that the new model tends to give the highest dose to the bladder wall surface; however, the results are essentially similar to those provided by the model of Chen et al. (4) (Model D). When compared with the MIRD 5 (Revised) (Model A) for an initial volume of 200 ml, values for the new model are approximately 57% higher (range 30%–83% higher). The Snyder and Ford (12) (Model B) and Diffey and Hilson (16) (Model C) models provide roughly identical results

for dose to the bladder wall that are, in general, slightly less than those given by the new model.

Each radiopharmaceutical has a unique time-activity curve for bladder activity. This variability, when combined with a nonuniform voiding schedule and analyzed in terms of initial bladder volume and first bladder voiding time, may be used to predict the optimum first voiding time and most desirable hydration states. Large initial bladder volumes and higher rates of urine flow into the bladder result in lower total bladder wall dose. Earlier first voiding times do not necessarily result in lower total bladder wall doses. In fact, the results indicate that the optimum first voiding time is from 40 min to 3 hr after administration, depending on the radiopharmaceutical. The optimum first void time ( $T_{1m}$ ) does not appear to be sensitive to the model used.

Electron dose decreases rapidly with increasing depth in the wall at a gradient determined by the electron energy spectrum. For most nuclear medicine radiopharmaceuticals, 90% of the energy is deposited within 0.1 cm of the bladder interior wall surface. An exception is  $^{124}\text{I}$ , potentially a contaminant in  $^{123}\text{I}$ . Other high-energy beta emitters such as  $^{90}\text{Y}$  or other therapy agents, however, might contribute a significant dose deep into the bladder wall and possibly even into surrounding tissues.

## ACKNOWLEDGMENTS


We gratefully acknowledge the assistance of William S. Kassing in preparing the figures and tables for this revised Pamphlet.

## REFERENCES


- Thomas SR, Stabin MG, Chen C-T, Samaratunga RC. MIRD Pamphlet No. 14: a Dynamic Urinary Bladder Model for Radiation Dose, Calculations. *J Nucl Med* 1992;33:783–802.
- [Erratum]. *J Nucl Med* 1994;35:73.
- Dowd MT, Chen C-T, Wendel MJ, Faulhaber PJ, Cooper MD. Radiation dose to the bladder wall from  $^{2-18}\text{F}$ fluoro-2-deoxy-D-glucose in adult humans. *J Nucl Med* 1991;32:707–712.
- Chen C-T, Harper PV, Lathrop KA. A simple dynamic model for calculating radiation absorbed dose to the bladder wall. In: Schlaefke-Stelson AT, Watson EE, eds. *Fourth International Radiopharmaceutical Dosimetry Symposium*, Nov. 5–8, 1985, Oak Ridge, TN: CONF-851113-(DE86010102), 587–612.
- Snyder WS, Ford MR, Warner GG. MIRD Pamphlet No. 5 (Revised): estimates of specific absorbed fractions for photon sources uniformly distributed in various organs of heterogeneous phantom. New York: The Society of Nuclear Medicine; 1978.
- Cristy M, Eckerman KF. *Specific absorbed fractions of energy at various ages from internal photon sources. I. Methods*. ORNL Publ. No. TM-8381/V1. 1987.
- Cloutier RJ, Smith SA, Watson EE, et al. Dose to the fetus from radionuclides in the bladder. *Health Phys* 1973;25:147–161.
- Loevinger R, Budinger TF, Watson EE. MIRD primer for absorbed dose calculations. New York: The Society of Nuclear Medicine; 1988.
- Snyder WS, Ford MR, Warner GG, Watson SB. MIRD Pamphlet No. 11: “S,” absorbed dose per unit cumulated activity for selected radionuclides and organs. New York: The Society of Nuclear Medicine; 1975.
- Snyder WS, Ford MR, Warner GG, Watson SB. A tabulation of dose equivalent per microcurie-day for source and target organs of an adult for various radionuclides. ORNL 5000. Oak Ridge TN: Oak Ridge National Laboratory; 1975.
- Loevinger R, Japha EM, Brownell GL. Discrete radioisotope sources. In: Hine GJ, Brownell GL, eds. *Radiation dosimetry*. New York: Academic Press; 1956:693–799.
- Snyder WS, Ford MR. Estimation of dose to the urinary bladder and to the gonads. In: Cloutier RJ, Coffey JL, Snyder WS, Watson EE, eds. *Radiopharmaceutical dosimetry symposium*, HEW Publication (FDA) 76-8044, 1976. Oak Ridge, TN, April 26–29, 1976. 313–350.
- Berger MJ. MIRD Pamphlet No. 7: distribution of absorbed dose around point sources of electrons and beta particles in water and other media. *J Nucl Med* 1971;12(suppl 5).
- Berger MJ. *Beta-ray dosimetry calculations with the use of point kernels in medical radionuclides, radiation dose and effects*. AEC Symposium Series No. 20. USAEC Division of Technical Information, 1970.
- Smith EM, Warner GG. Practical methods of dose reduction to the bladder wall. In: *Radiopharmaceutical dosimetry symposium*. Oak Ridge, TN, April 26–29, 1976. 351–359.
- Diffey B, Hilson A. Absorbed dose to the bladder form.  $^{99m}\text{Tc}$ -DTPA [Letter]. *Br J Radiol* 1976;49:196–198.
- Powell GR, Chen C-T. Radiation absorbed dose to bladder walls from positron emitters in the bladder content. *Med Phys* 1987;14:1079–1086.
- Bochkarev VV, Radzievsky GB, Timofeev LV, Demiano DA. Distribution and absorbed energy from a point beta-source in a tissue equivalent medium. *Int J Appl Radiat Isot* 1972;23:493.
- Unnikrishnan K. Dose to the urinary bladder from radionuclides in urine. *Phys Med Biol* 1974;19:329–340.
- Dimitriou P, Fretzayas A, Nicolaoudou P, et al. Estimates of dose to the bladder during direct radionuclide cystography: concise communication. *J Nucl Med* 1984;25:792–795.
- Smith T, Veall N, Wotton R. Bladder wall dose from administered radiopharmaceuticals: the effects of variations in urine flow rate, voiding interval, and initial bladder content. *Radiat Prot Dosim* 1982;2:183–189.
- Jones S, Alavi A, Christman D, Montanez I, Wolf A, Reivich M. The radiation dosimetry of  $2-[^18\text{F}]$ fluoro-2-deoxy-D-glucose in man. *J Nucl Med* 1982;23:613–617.
- Thomas SR, Atkins HL, McAfee JG, et al. MIRD Dose Estimate Report No. 12: radiation absorbed dose from  $\text{Tc}-99\text{m}$  diethylenetriaminepentacetic acid (DTPA). *J Nucl Med* 1984;25:503–505.
- Lathrop KA, Atkins HL, Berman M, et al. Summary of current radiation dose estimates to normal humans from  $\text{Tc}-99\text{m}$  as sodium pertechnetate. *J Nucl Med* 1976;17:74–77.
- Weber DA, Makler PT Jr, Watson EE, et al. Radiation absorbed dose from technetium-99-labeled bone imaging agents. *J Nucl Med* 1989;30:1117–1122.
- Soundy RG, Tyrell DA, Pickett RD, Stabin MG. The radiation dosimetry of  $\text{Tc}-99\text{m}$  exometazime. *Nucl Med Commun* 1990;11:791–799.
- Radiation dose to patients from radiopharmaceuticals (technetium-gluconate, glucoheptonate). In: ICRP Publication No. 53, a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:193–194.
- Radiation dose to patients from radiopharmaceuticals (technetium-labelled albumin (HSA)). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:173.
- Radiation dose to patients from radiopharmaceuticals (technetium-labelled erythrocytes). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:209–210.
- Radiation dose to patients from radiopharmaceuticals (technetium-labelled MIBI). In: ICRP Publication No. 62: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Tarrytown, NY: Pergamon Press, Inc.; 1993: 21–24.
- Berman M, Braverman LE, Burke J, et al. Summary of current radiation dose estimates to humans from I-123, I-124, I-125, I-126, I-130, I-131, and I-132 as sodium iodide. *J Nucl Med* 1975;16:857–860.
- Lindmo T, Skerrettin A, Nakken K. An examination of different mathematical models for renal function as measured by  $^{131}\text{I}$ -hippuran renography. *Med Phys* 1974;1:193–197.
- Radiation dose to patients from radiopharmaceuticals (iothalamate). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:315–316.
- Radiation dose to patients from radiopharmaceuticals (indium-DTPA). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:237–240.
- Radiation dose to patients from radiopharmaceuticals (strontium). In: ICRP Publication No. 53: a report of Task Group of Committee 2 of the International Commission on Radiation Protection. Elmsford, NY: Pergamon Press, Inc.; 1988:169–171.
- Weber DA, Eckerman KF, Dillman LT, et al. *MIRD: radionuclide data and decay schemes*. New York: The Society of Nuclear Medicine; 1989.

## APPENDIX A


DTPA calculations for the various models are shown in Figures A1–A4 and Tables A1–A4. Calculations for the new model are shown in Figures A5–A24 and Tables A5–A24.




**FIGURE A1.** Model A [MIRD Pamphlet No. 5 Revised (5)],  $^{99m}\text{Tc}$ -DTPA. Dose per unit administered activity to the urinary bladder wall surface as a function of first void time ( $T_1$ ) (constant volume). Urine entry rate  $U(t) = 1.25 \text{ ml/min}$  (constant at all times). Voiding schedule = every 3 hr after initial void, 10 voids total included in the dose calculation and no nighttime gap.



**FIGURE A3.** Model C [Difley and Hilson (16)],  $^{99m}\text{Tc}$ -DTPA. Dose per unit administered activity to the urinary bladder wall surface as a function of first void time ( $T_1$ ) for various values of initial bladder contents ( $V_0$ ). Urine entry rate  $U(t)$  and voiding schedule were the same as those in Figure A1.



**FIGURE A2.** Model B [Snyder and Ford (12)],  $^{99m}\text{Tc}$ -DTPA. Dose per unit administered activity to the urinary bladder wall surface as a function of first void time ( $T_1$ ) for various values of initial bladder contents ( $V_0$ ). Urine entry rate  $U(t)$  and voiding schedule were the same as those in Figure A1.



**FIGURE A4.** Model D [Chen et al. (4)],  $^{99m}\text{Tc}$ -DTPA. Dose per unit administered activity to the urinary bladder wall surface as a function of first void time ( $T_1$ ) for various values of initial bladder contents ( $V_0$ ). Urine entry rate  $U(t)$  and voiding schedule were the same as those in Figure A1.

**TABLE A1**

Technetium-99m-DTPA Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq) Model A: MIRD, 1978 (5)

First void time (min)								
20	40	60	80	100	120	140	160	180
0.033	0.030	0.029	0.030	0.032	0.035	0.039	0.044	0.049

**TABLE A2**  
Technetium-99m-DTPA Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)  
Model B: Snyder and Ford (12)

$V_0$ (ml)	First void time (min)								
	20	40	60	80	100	120	140	160	180
10	0.084	0.078	0.076	0.076	0.077	0.079	0.081	0.084	0.088
50	0.078	0.070	0.065	0.063	0.063	0.064	0.066	0.068	0.071
100	0.075	0.065	0.060	0.057	0.056	0.056	0.057	0.059	0.061
200	0.070	0.061	0.054	0.051	0.049	0.048	0.048	0.049	0.050
500	0.062	0.053	0.046	0.042	0.038	0.037	0.035	0.035	0.035

$V_0$  = initial Bladder Volume (ml).

**TABLE A3**  
Technetium-99m-DTPA Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)  
Model C: Diffey and Hilson (16)


$V_0$ (ml)	First void time (min)								
	20	40	60	80	100	120	140	160	180
10	0.085	0.079	0.077	0.077	0.078	0.080	0.082	0.084	0.087
50	0.078	0.070	0.065	0.063	0.063	0.064	0.065	0.067	0.069
100	0.074	0.065	0.059	0.056	0.055	0.055	0.055	0.056	0.058
200	0.069	0.060	0.053	0.049	0.047	0.046	0.045	0.046	0.046
500	0.061	0.051	0.045	0.040	0.037	0.035	0.034	0.033	0.033

$V_0$  = initial bladder volume (ml).


**TABLE A4**  
Technetium-99m-DTPA Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)  
Model D: Chen et al. (4)

$V_0$ (ml)	First void time (min)								
	20	40	60	80	100	120	140	160	180
10	0.091	0.085	0.083	0.083	0.084	0.086	0.089	0.091	0.094
50	0.085	0.076	0.071	0.069	0.068	0.069	0.071	0.073	0.075
100	0.081	0.071	0.064	0.061	0.060	0.060	0.061	0.062	0.064
200	0.076	0.065	0.058	0.054	0.051	0.050	0.050	0.051	0.052
500	0.066	0.056	0.049	0.044	0.041	0.039	0.038	0.037	0.037


$V_0$  = initial bladder volume (ml).




**FIGURE A5.** New model for  $^{18}\text{F}$ -FDG. Dose per unit administered activity to the urinary bladder wall surface.




**FIGURE A8.** New model for  $^{99\text{m}}\text{Tc}$ -HEDP. Dose per unit administered activity to the urinary bladder wall surface.




**FIGURE A6.** New model for  $^{99\text{m}}\text{Tc}$ -DTPA. Dose per unit administered activity to the urinary bladder wall surface.



**FIGURE A9.** New model for  $^{99\text{m}}\text{Tc}$ -MDP. Dose per unit administered activity to the urinary bladder wall surface.



**FIGURE A7.** New model for  $^{99\text{m}}\text{Tc}$ -pertechnetate. Dose per unit administered activity to the urinary bladder wall surface.



**FIGURE A10.** New model for  $^{99\text{m}}\text{Tc}$ -HMPAO. Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A11. New model for  $^{99m}\text{Tc}$ -glucoheptonate. Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A14. New model for  $^{99m}\text{Tc}$ -RBCs. Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A12. New model for  $^{99m}\text{Tc}$ -MAG3. Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A15. New model for  $^{99m}\text{Tc}$ -MIBI (rest). Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A13. New model for  $^{99m}\text{Tc}$ -HSA. Dose per unit administered activity to the urinary bladder wall surface.







FIGURE A16. New model for  $^{99m}\text{Tc}$ -MIBI (stress). Dose per unit administered activity to the urinary bladder wall surface.




**FIGURE A17.** New model for  $^{123}\text{I}$ -NaI. Dose per unit administered activity to the urinary bladder wall surface.




**FIGURE A20.** New model for  $^{124}\text{I}$ -OIH. Dose per unit administered activity to the urinary bladder wall surface.




**FIGURE A18.** New model for  $^{131}\text{I}$ -NaI. Dose per unit administered activity to the urinary bladder wall surface.



**FIGURE A21.** New model for  $^{131}\text{I}$ -OIH. Dose per unit administered activity to the urinary bladder wall surface.



**FIGURE A19.** New model for  $^{123}\text{I}$ -OIH. Dose per unit administered activity to the urinary bladder wall surface.



**FIGURE A22.** New model for  $^{125}\text{I}$ -iothalamate. Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A23. New model for  $^{111}\text{In}$ -DTPA. Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A26. Technetium-99m-DTPA. Fractional bladder activity  $[A(t)/A_0]$  from Eq.2] as a function of time.  $V_0 = 100 \text{ ml}$ ,  $T_1 = 60 \text{ min}$  and  $U(t) = 1.0/0.5 \text{ ml min}^{-1}$  (day/night).




FIGURE A24. New model for  $^{89}\text{Sr}$ -SrCl. Dose per unit administered activity to the urinary bladder wall surface.




FIGURE A27. Fluorine-18-FDG. Electron dose per unit administered activity as a function of distance into the bladder wall.  $V_0 = 200 \text{ ml}$  and  $T_1 = 60 \text{ min}$ .




FIGURE A25. Fluorine-18-FDG. Fractional bladder activity  $[A(t)/A_0]$  from Eq.2] as a function of time.  $V_0 = 100 \text{ ml}$ ,  $T_1 = 60 \text{ min}$  and  $U(t) = 1.0/0.5 \text{ ml min}^{-1}$  (day/night).




FIGURE A28. Technetium-99m-DTPA. Electron dose per unit administered activity as a function of distance into the bladder wall.  $V_0 = 200 \text{ ml}$  and  $T_1 = 160 \text{ min}$ .

**TABLE A5**  
**Fluorine-18-FDG**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.61	0.35	0.24	0.54	0.31	0.23	0.60	0.36	0.26	0.65	0.40	0.29
50	0.38	0.24	0.18	0.27	0.18	0.14	0.30	0.22	0.17	0.34	0.25	0.20
100	0.33	0.21	0.16	0.19	0.13	0.11	0.20	0.15	0.13	0.23	0.18	0.15
200	0.31	0.19	0.14	0.13	0.094	0.077	0.12	0.10	0.089	0.14	0.12	0.10
500	0.29	0.18	0.13	0.091	0.063	0.051	0.066	0.055	0.050	0.073	0.064	0.059

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A6**  
**Technetium-99m-DTPA**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.19	0.11	0.077	0.18	0.10	0.071	0.18	0.10	0.072	0.19	0.11	0.079
50	0.17	0.097	0.070	0.14	0.082	0.060	0.13	0.079	0.059	0.13	0.084	0.064
100	0.16	0.093	0.067	0.12	0.074	0.055	0.10	0.067	0.051	0.10	0.069	0.054
200	0.16	0.091	0.066	0.11	0.068	0.050	0.087	0.056	0.043	0.080	0.055	0.045
500	0.15	0.089	0.064	0.11	0.063	0.046	0.073	0.045	0.035	0.060	0.041	0.033

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A7**  
**Technetium-99m-Pertechnetate**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.055	0.031	0.022	0.054	0.030	0.021	0.054	0.030	0.021	0.054	0.030	0.022
50	0.052	0.029	0.021	0.049	0.028	0.020	0.046	0.027	0.020	0.045	0.027	0.020
100	0.051	0.029	0.021	0.047	0.027	0.019	0.043	0.025	0.019	0.041	0.025	0.018
200	0.051	0.029	0.021	0.046	0.026	0.019	0.041	0.024	0.017	0.037	0.022	0.017
500	0.051	0.029	0.020	0.045	0.026	0.018	0.038	0.022	0.016	0.034	0.020	0.015

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A8**  
**Technetium-99m-HEDP**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.15	0.082	0.058	0.14	0.078	0.055	0.13	0.074	0.053	0.14	0.076	0.054
50	0.14	0.079	0.057	0.12	0.072	0.052	0.11	0.064	0.047	0.10	0.064	0.047
100	0.14	0.078	0.056	0.12	0.069	0.050	0.097	0.058	0.043	0.088	0.056	0.042
200	0.14	0.078	0.056	0.11	0.066	0.048	0.087	0.053	0.039	0.074	0.048	0.037
500	0.14	0.077	0.055	0.11	0.064	0.046	0.079	0.047	0.035	0.062	0.039	0.030

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A9**  
**Technetium-99m-MDP**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.13	0.075	0.053	0.13	0.070	0.049	0.12	0.066	0.047	0.12	0.069	0.049
50	0.13	0.072	0.052	0.11	0.063	0.045	0.092	0.055	0.041	0.091	0.056	0.042
100	0.12	0.071	0.051	0.10	0.059	0.043	0.079	0.049	0.037	0.074	0.048	0.037
200	0.12	0.070	0.051	0.096	0.056	0.041	0.070	0.043	0.033	0.060	0.040	0.031
500	0.12	0.070	0.050	0.093	0.054	0.039	0.061	0.037	0.028	0.048	0.031	0.025

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A10**  
**Technetium-99m-HMPAO**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.066	0.037	0.026	0.060	0.033	0.024	0.061	0.035	0.025	0.066	0.038	0.028
50	0.055	0.032	0.023	0.045	0.027	0.020	0.043	0.027	0.020	0.046	0.029	0.022
100	0.053	0.031	0.022	0.040	0.024	0.018	0.035	0.023	0.017	0.036	0.024	0.019
200	0.051	0.030	0.022	0.036	0.022	0.016	0.029	0.019	0.015	0.029	0.020	0.016
500	0.050	0.029	0.021	0.033	0.020	0.014	0.025	0.015	0.012	0.022	0.015	0.012

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A11**  
**Technetium-99m-Glucoheptonate**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.18	0.10	0.072	0.16	0.090	0.064	0.17	0.10	0.072	0.19	0.11	0.082
50	0.14	0.082	0.060	0.11	0.065	0.049	0.11	0.071	0.055	0.12	0.081	0.063
100	0.13	0.077	0.056	0.087	0.055	0.042	0.083	0.056	0.045	0.090	0.064	0.052
200	0.12	0.073	0.053	0.075	0.046	0.035	0.063	0.044	0.035	0.066	0.048	0.040
500	0.12	0.070	0.051	0.065	0.040	0.030	0.047	0.032	0.025	0.044	0.032	0.027

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A12**  
**Technetium-99m-MAG3**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.36	0.20	0.14	0.34	0.20	0.15	0.40	0.24	0.18	0.44	0.28	0.21
50	0.17	0.11	0.084	0.16	0.11	0.088	0.20	0.14	0.12	0.24	0.17	0.14
100	0.13	0.085	0.065	0.10	0.076	0.063	0.13	0.10	0.087	0.16	0.13	0.11
200	0.11	0.069	0.053	0.067	0.051	0.043	0.082	0.068	0.060	0.10	0.087	0.077
500	0.093	0.058	0.044	0.039	0.030	0.025	0.041	0.036	0.034	0.054	0.048	0.045

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A13**  
**Technetium-99m-HSA**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.0063	0.0035	0.0025	0.0062	0.0035	0.0025	0.0062	0.0034	0.0024	0.0062	0.0035	0.0025
50	0.0060	0.0034	0.0024	0.0058	0.0033	0.0023	0.0055	0.0032	0.0023	0.0054	0.0032	0.0023
100	0.0060	0.0034	0.0024	0.0056	0.0032	0.0023	0.0053	0.0030	0.0022	0.0050	0.0030	0.0022
200	0.0059	0.0033	0.0024	0.0055	0.0031	0.0022	0.0050	0.0029	0.0021	0.0047	0.0028	0.0020
500	0.0059	0.0033	0.0024	0.0054	0.0031	0.0022	0.0048	0.0028	0.0020	0.0044	0.0026	0.0019

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A14**  
**Technetium-99m-RBCs**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.026	0.015	0.010	0.026	0.014	0.010	0.026	0.014	0.010	0.026	0.014	0.010
50	0.025	0.014	0.010	0.024	0.014	0.010	0.023	0.013	0.010	0.023	0.013	0.010
100	0.025	0.014	0.010	0.024	0.013	0.010	0.022	0.013	0.0092	0.021	0.012	0.0091
200	0.025	0.014	0.010	0.023	0.013	0.0094	0.021	0.012	0.0089	0.020	0.012	0.0086
500	0.025	0.014	0.010	0.023	0.013	0.0092	0.020	0.012	0.0084	0.019	0.011	0.0080

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A15**  
**Technetium-99m-MIBI (Rest)**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.025	0.014	0.010	0.025	0.014	0.010	0.024	0.014	0.010	0.025	0.014	0.010
50	0.024	0.013	0.010	0.022	0.013	0.0092	0.021	0.012	0.0089	0.021	0.012	0.0089
100	0.023	0.013	0.0094	0.022	0.012	0.0089	0.020	0.012	0.0085	0.019	0.011	0.0084
200	0.023	0.013	0.0093	0.021	0.012	0.0086	0.019	0.011	0.0080	0.017	0.010	0.0077
500	0.023	0.013	0.0093	0.021	0.012	0.0084	0.018	0.010	0.0075	0.016	0.0094	0.0070

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A16**  
**Technetium-99m-MIBI (Stress)**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.022	0.012	0.0086	0.022	0.012	0.0085	0.021	0.012	0.0084	0.021	0.012	0.0086
50	0.021	0.012	0.0084	0.020	0.011	0.0080	0.019	0.011	0.0078	0.018	0.011	0.0078
100	0.021	0.012	0.0083	0.019	0.011	0.0078	0.018	0.010	0.0074	0.017	0.010	0.0074
200	0.020	0.011	0.0082	0.019	0.011	0.0076	0.017	0.010	0.0071	0.015	0.0092	0.0068
500	0.020	0.011	0.0081	0.018	0.010	0.0074	0.016	0.0091	0.0066	0.014	0.0083	0.0062

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A17**  
Iodine-123-NaI  
Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.26	0.14	0.10	0.25	0.14	0.10	0.25	0.14	0.10	0.25	0.14	0.10
50	0.25	0.14	0.10	0.23	0.13	0.095	0.22	0.13	0.092	0.22	0.13	0.093
100	0.24	0.14	0.10	0.23	0.13	0.092	0.21	0.12	0.088	0.20	0.12	0.088
200	0.24	0.13	0.10	0.22	0.13	0.090	0.20	0.12	0.084	0.19	0.11	0.082
500	0.24	0.13	0.10	0.22	0.12	0.088	0.19	0.11	0.080	0.17	0.10	0.075

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A18**  
Iodine-131-NaI  
Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	1.8	0.94	0.64	1.8	0.93	0.64	1.8	0.93	0.63	1.8	0.93	0.64
50	1.8	0.92	0.63	1.7	0.89	0.61	1.6	0.87	0.60	1.6	0.86	0.60
100	1.7	0.91	0.62	1.7	0.87	0.60	1.6	0.84	0.58	1.5	0.82	0.57
200	1.7	0.91	0.62	1.6	0.86	0.59	1.5	0.81	0.56	1.5	0.78	0.55
500	1.7	0.90	0.62	1.6	0.85	0.58	1.5	0.79	0.54	1.4	0.74	0.52

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A19**  
Iodine-123-OIH  
Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	0.73	0.40	0.28	0.69	0.40	0.29	0.79	0.48	0.36	0.90	0.56	0.42
50	0.36	0.22	0.17	0.33	0.22	0.18	0.41	0.29	0.24	0.50	0.36	0.29
100	0.27	0.17	0.13	0.21	0.15	0.13	0.27	0.21	0.18	0.35	0.27	0.22
200	0.23	0.14	0.11	0.14	0.10	0.088	0.17	0.14	0.12	0.22	0.18	0.16
500	0.20	0.12	0.091	0.082	0.061	0.053	0.087	0.076	0.070	0.12	0.10	0.10

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A20**  
Iodine-124-OIH  
Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)
10	4.3	2.3	1.5	4.0	2.2	1.6	4.6	2.7	2.0	5.2	3.1	2.3
50	2.1	1.3	0.93	1.9	1.2	1.0	2.3	1.6	1.3	2.8	2.0	1.5
100	1.6	1.0	0.73	1.2	0.84	0.68	1.5	1.1	0.93	1.9	1.4	1.2
200	1.3	0.80	0.60	0.77	0.56	0.46	0.93	0.74	0.64	1.2	1.0	0.84
500	1.1	0.68	0.50	0.46	0.33	0.27	0.45	0.39	0.35	0.61	0.53	0.48

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A21**  
**Iodine-131-OIH**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	
10	3.7	1.9	1.3	3.4	1.9	1.3	3.9	2.3	1.6	4.4	2.6	1.9
50	1.8	1.0	0.76	1.6	1.0	0.78	1.9	1.3	1.0	2.3	1.6	1.2
100	1.3	0.81	0.60	1.0	0.68	0.55	1.2	0.90	0.74	1.6	1.1	0.93
200	1.1	0.66	0.49	0.63	0.45	0.37	0.74	0.58	0.49	1.0	0.75	0.64
500	1.0	0.56	0.41	0.37	0.26	0.21	0.35	0.29	0.26	0.46	0.39	0.35

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A22**  
**Iodine-125-lothalamate**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	
10	0.45	0.25	0.18	0.43	0.24	0.17	0.42	0.23	0.17	0.44	0.25	0.18
50	0.41	0.23	0.17	0.36	0.21	0.15	0.33	0.20	0.14	0.33	0.20	0.15
100	0.40	0.22	0.16	0.33	0.19	0.14	0.28	0.17	0.13	0.27	0.18	0.14
200	0.39	0.22	0.16	0.32	0.18	0.13	0.25	0.15	0.12	0.22	0.15	0.12
500	0.39	0.22	0.16	0.30	0.17	0.13	0.22	0.13	0.10	0.18	0.12	0.092

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A23**  
**Indium-111-DTPA**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	
10	0.87	0.49	0.35	0.83	0.46	0.33	0.81	0.46	0.33	0.85	0.48	0.35
50	0.78	0.45	0.33	0.69	0.40	0.29	0.63	0.38	0.28	0.63	0.40	0.30
100	0.76	0.44	0.32	0.64	0.38	0.28	0.54	0.34	0.26	0.52	0.34	0.27
200	0.75	0.43	0.31	0.60	0.35	0.26	0.48	0.30	0.23	0.43	0.29	0.23
500	0.74	0.43	0.31	0.58	0.34	0.25	0.42	0.26	0.20	0.34	0.23	0.18

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).

**TABLE A24**  
**Sr-89-Chloride**  
**Dose per Unit Administered Activity to the Bladder Wall Surface (mGy/MBq)**

V <sub>0</sub> (ml)	First void time (min)											
	20			60			120			180		
(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	(a)	(b)	(c)	
10	3.9	2.0	1.3	3.9	2.0	1.3	3.9	2.0	1.3	3.9	2.0	1.3
50	3.9	2.0	1.3	3.8	1.9	1.3	3.8	1.9	1.3	3.7	1.9	1.3
100	3.9	2.0	1.3	3.8	1.9	1.3	3.7	1.9	1.3	3.7	1.9	1.3
200	3.9	1.9	1.3	3.8	1.9	1.3	3.7	1.9	1.3	3.6	1.8	1.2
500	3.8	1.9	1.3	3.8	1.9	1.3	3.6	1.8	1.2	3.5	1.8	1.2

V<sub>0</sub> = initial bladder volume (ml). Bladder filling rates (ml/min) were: (a) 0.5/0.25 (day/night); (b) 1.0/0.50 (day/night); and (c) 1.5/0.75 (day/night).